

2-way switch for card with 1 micro switch and light indicator 250V~ grey Simon 75

REF. 75526-35



BASIC INFORMATION

DESCRIPTION

2-way switch for card with 1 microswitch and indicator light has a current of 6 A and a voltage of 250 V~, comes in grey colour, it belongs to the wide and extensive range of products of the Simon 75 brand. Fast terminal connection and works with card. It is recommended the installation combined with a contactor / relay. If this is not the case, the maximum current of the 2-way switch is 6° (inductive 2A), it is very important when position, place the frame to know that the tabs of the same. It has a signal function with a consumption of 1 mA, for its installation it will suffice to apply pressure or place on the surface, the wire is 0.5 mm, the material of manufacture is to socket of metal components with halogen-free insulation and thermoplastic trims that are designed to reach temperatures that can oscillate without any inconvenience between 5 and 40°, and can support up to a maximum of between -25 and 50° C. Complies with the regulation UNE-EN 60669-1: 1996 + 60669-2-1: 2002 + 60669-2-3: 1999. For hygiene, clean with a soft, dry cloth, do not use abrasive cloths and / or abrasive cleaners containing chlorine.

FINISH

Grey

COMPATIBILITY

Simon 75 frames

PACKAGING CONTENTS

Mechanism and cover

REMARKS

A contactor must be installed at the output of the mechanism. If this is not done, the maximum current of the switch is 10 A resistive (1.5 A inductive). It is recommended to protect the faston connectors with a heat shrink sleeve.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

INDICATOR FUNCTION

Yes

NOMINAL VOLTAGE (V~)

250 V~

CABLE SECTION ADMITTED (MM)

0,5 mm

CURRENT (A)

10 (1,5 ind.) A

OPERATING TEMPERATURE

RANGE (°C)

5 - 40 °C

CONSUMPTION INDICATOR (mA)

1 mA

IP RATING

IP20

POWER SUPPLY (V~)

250 V~

NUMBER OF POSSIBLE ELEMENTS

1 element

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

FREQUENCY

50 Hz

TYPE OF MECHANISM

Card

VERSION

Single

INSTALLATION AND MAINTENANCE

CLAW

Simon 27

INSTALLATION DIRECTION

Horizontal, Vertical

TYPE OF TERMINAL

CONNECTION - FUNCTION 1

Faston

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

INSTALLATION TYPE

Suitable for surface and flush mounting

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN IEC 61058-1:2018 | EN 61058-1-1:2016 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
1517738

UNITARY PACKAGING VOLUME
UNIT
MMQ

UNITARY PACKAGING GROSS
WEIGHT
0.08

PRODUCT NET WEIGHT
0.08

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING EAN
8421053017968

UNITS CONTAINED PACKAGING
5

PACKAGING HEIGHT
82

PACKAGING WIDTH
83

PACKAGING LENGTH
223

PACKAGING MEASUREMENT
UNIT
MMT

PACKAGING VOLUME
3017190

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.4

PACKAGING NET WEIGHT
0.4

PACKAGING WEIGHT UNIT
KGM