# Complete kit with 2xUSB charger and 3 schuko socket outlets white S400 Top

REF. **42423000-130**



## BASIC INFORMATION

### DESCRIPTION

Simon offers a product designed for those workspaces that require all connections in one place. Within the 400 series, we find this complete table kit with a 2 x USB charger and 3 schuko sockets in white. A cutting-edge product with a white finish, the trim cover is made of painted steel with a very resistant anodized aluminum profile that withstands impacts. Simon provides extra safety in the unlikely event of combustion; its covers and fastenings prevent flames from spreading as they are made from self-extinguishing thermoplastic. A product created for intensities of 16 amperes and a voltage of 250 volts.

### FINISH

White

### MATERIAL

Metal

### COMPATIBILITY

Functions of the Simon 400 range, combinable with the Simon Electric Cabling range.

### PACKAGING CONTENTS

Pre-wired profile, table-top supports, rear trim cover and installation manual.

### ETIM CLASS

EC002759

## TECHNICAL INFORMATION

### AVAILABLE MARKET
CE

### DIELECTRIC STRENGTH
No holes or contours, with 2000V at 50 Hz for 1 minute

### MAX TEMP DURING CONSTRUCTION WORK (°C)
+60° C

### FORMAT
Schuko

### HEAT RESISTANCE (°C)
+70°C (according to standard IEC 60670)

### IK CLASSIFICATION
07

### INSULATION RESISTANCE (V-MΩ)
>5 MΩ a 500 V

### CURRENT (A)
16 A

### IP RATING
IP30

### MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60° C

### NOMINAL VOLTAGE (V~)
250 V~

### OPERATING TEMPERATURE RANGE (°C)
-5...+60

### TYPE OF POWER SUPPLY CONNECTOR
Wieland® GST 18i male 3-pole overhead connector with 22 cm patch cord

### RAL
9016

### NUMBER OF SOCKETS
3 sockets for standard current circuit

### NUMBER OF USB CHARGERS
1

### VERSION
4 elements

## INSTALLATION AND MAINTENANCE

### CLAW RANGE OF OPERATION (MM)
Between 16 and 40 mm

### EXTINGUISHING (°C)
+70 °C (according to standard IEC 60670)

### TYPE OF FASTENING
By tightening existing clamps in the fastening bracket.

### INSTALLATION TYPE
Suitable for fixing to furniture.

### REMOVAL OF THE PLATE
Only with tool

### SECURING POSSIBILITIES
Using clips included in the fastening brackets

### MOUNTING WITHOUT ACCESSORIES
Supplied with all necessary materials for installation.

## REGULATIONS

### REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

## LOGISTICS INFORMATION

### UNITARY EAN CODE
8421053275047

### UNITARY PACKAGING HEIGHT
0

### UNITARY PACKAGING WIDTH
0

### UNITARY PACKAGING LENGTH
0

### UNITARY PACKAGING MEASUREMENT UNIT
MMT

### UNITARY PACKAGING VOLUME
0

### UNITARY PACKAGING VOLUME UNIT
MMQ

### UNITARY PACKAGING GROSS WEIGHT
0.85

### PRODUCT NET WEIGHT
0.85

### UNITARY PACKAGING WEIGHT UNIT
KGM

### PACKAGING EAN
8421053275047

### UNITS CONTAINED PACKAGING
1

### PACKAGING HEIGHT
90

### PACKAGING WIDTH
116

### PACKAGING LENGTH
213

### PACKAGING MEASUREMENT UNIT
MMT

### PACKAGING VOLUME
2223720

### PACKAGING VOLUME UNIT
MMQ

### PACKAGING GROSS WEIGHT
0

### PACKAGING NET WEIGHT
0.85

### PACKAGING WEIGHT UNIT
KGM