

## Downlight 725.28 3000K DALI

REF. 72528330-883



### BASIC INFORMATION

#### APPLICATION

General lighting

#### PACKAGING CONTENTS

1 unit

## TECHNICAL INFORMATION

### FREQUENCY

50 - 60 Hz

### CRI

80

### LUMENS/W

2375 lm/23W

### IP RATING

IP44

### ELECTRICAL CLASS

Type 2

### OPTICS

General

### OPERATING TEMPERATURE RANGE (°C)

-10 - 35 °C

### L70 (°C)

54.000 h at 25°C

### PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

### POWER SUPPLY (V~)

220/240 V~

### LIGHT BEAM APERTURE ANGLE (°)

120°

### POWER (W)

23 W

### COLOR TEMPERATURE (K)

3000 K

### LIGHTING EFFICIENCY (LM/W)

103 lm/W

### SERVICE LIFE

50.000 h

### CONTROL

DALI

### LUMENS (LM)

2375 lm

### CHROMATICS CRI ICONS

CRI  
80

## INSTALLATION AND MAINTENANCE

### INSTALLATION TYPE

Flush mount

## REGULATIONS

### WARRANTY

3 years

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053282519

### UNITARY PACKAGING HEIGHT

5.5

### UNITARY PACKAGING WIDTH

26.5

### UNITARY PACKAGING LENGTH

29

### UNITARY PACKAGING MEASUREMENT UNIT

MMT

### UNITARY PACKAGING VOLUME

4226.75

### UNITARY PACKAGING VOLUME UNIT

MMQ

### UNITARY PACKAGING GROSS WEIGHT

0.9

### PRODUCT NET WEIGHT

0.586

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053282519

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

5.5

### PACKAGING WIDTH

26.5

### PACKAGING LENGTH

29

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

4226.75

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

0.9

### PACKAGING NET WEIGHT

0.586

### PACKAGING WEIGHT UNIT

KGM