

## Set of 2 push-button switches for blinds 10A 250V~ with electrical latching system white Simon 27 Play

REF. 27332-35



## BASIC INFORMATION

### DESCRIPTION

Having electrical systems in the blinds will allow us to make a comfortable to use them to the throughout the day. This situation, it is very important in large buildings bodies or the headquarters of companies private where the number of them and the is high traffic of people throughout the day. With the aim to meet this need was designed the group of 2 push buttons for blinds 10a 250V~ with electrical latching system in white finish of the Simon 27 Play series. Quick-terminal connection, rocker operation, suitable for surface and flush mounting, supports a cable section of 1.5 to 2.5 mm and the stripping of the wire 11 mm, includes engraving of the up / down blinds, manufactured with metal components with halogen-free thermoplastic insulation and thermoset trim and compatible with Marcos Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralizations and Simon 44 Aqua are some of the advantages of this push-button switch for blinds 45x45 mm

### FINISH

White

### COMPATIBILITY

Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations and Simon 44 Aqua frames

### PACKAGING CONTENTS

Mechanism with rockers

### ETIM CLASS

EC000044

### REMARKS

Mechanism fitted with security latching to prevent simultaneous operation.

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE

### IP RATING

IP20

### OPERATING TEMPERATURE

RANGE (°C)

5 - 40 °C

### CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

### LATCH TYPE

Electric

### STORAGE TEMPERATURE RANGE

(°C)

-25 - 50 °C

### NUMBER OF POSSIBLE ELEMENTS

1 element

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### VERSION

Double

### INDICATOR FUNCTION

No

### TYPE OF MECHANISM

Pivoting

### VOLTAGE (V~)

250 V~

### CURRENT (A)

10 A

## INSTALLATION AND MAINTENANCE

### CABLE STRIPPING NECESSARY (MM)

11

### CLAW

Simon 27

### INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, American and  
Centralisations

### INSTALLATION TYPE

Suitable for surface and flush  
mounting

### TYPE OF TERMINAL CONNECTION - FUNCTION 1

Fast

## REGULATIONS

### REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN 60669-1:2018 | EN IEC 63000:2018

## LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

38.4

UNITARY PACKAGING WIDTH

45.9

UNITARY PACKAGING LENGTH

45.7

UNITARY PACKAGING  
MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0.081

UNITARY PACKAGING VOLUME  
UNIT

DMQ

UNITARY PACKAGING GROSS  
WEIGHT

0.058

PRODUCT NET WEIGHT

0.042

UNITARY PACKAGING WEIGHT  
UNIT

KGM

PACKAGING EAN

8421053071700

UNITS CONTAINED PACKAGING

5

PACKAGING HEIGHT

55

PACKAGING WIDTH

105.5

PACKAGING LENGTH

158

PACKAGING MEASUREMENT  
UNIT

MMT

PACKAGING VOLUME

0.917

PACKAGING VOLUME UNIT

DMQ

PACKAGING GROSS WEIGHT

0.29

PACKAGING NET WEIGHT

0.21

PACKAGING WEIGHT UNIT

KGM