

Modular luminaire 720 Advance M4 120X30 NW CLC DALI

REF. 72061540-884



BASIC INFORMATION

DESCRIPTION

With a light of a white neutral, the luminaire 720 modular Advance M4 of the collection for indoor lighting of Simon, get the maximum functionality and innovation in a design that protects the environment. With constant light control (CLC), will take the maximum the natural light, balancing the use of light artificial; with interface of adjustment bidirectional DALI and comprising multiple LEDs ' s. With a luminous light flux 3400 lm for NW, and a consumption of 28 W, with translucent optics, in a dimension of 120 x 30. Its power supply is compatible with a voltage of 230 V AC and 50-60 Hz, and has a service life of 40,000 hours at 25 ° C to L90 and up to 100,000 hours for the L70. With a modern design of clean lines, it is designed for installation in false ceiling, visible hardware, with the versatility of being able to be installed flush mounted or surface-mounted.

DIFFUSER MATERIAL

PMMA

PACKAGING CONTENTS

1 unit

APPLICATION

General lighting

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DRIVER INCLUDED

Yes

LIGHTING EFFICIENCY (LM/W)

121 lm/W

IP RATING

IP44

ELECTRICAL CLASS

Type 2

LUMENS (LM)

3400 lm

OPERATING TEMPERATURE RANGE (°C)

40 °C maximum

INTEGRATED POWER SUPPLY

Yes

LUMENS/W

3400 lm/28W

POWER SUPPLY (V~)

230 V~

L70 (°C)

100,000 h at 25 °C

OPTICS

Translucent

COLOR TEMPERATURE (K)

4000 K

L90 (°C)

40,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

CONTROL

CLC,DALI

LIGHT BEAM APERTURE ANGLE (°)

120°

POWER (W)

28 W

CRI

82

COLOR TYPE

NW

SERVICE LIFE

50.000 h

CHROMATICS CRI ICONS

CRI
82

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Plaster ceiling, surface mount, concealed or semi-concealed profile.

MINIMUM INSTALLATION HEIGHT

120

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Quick connector

INSTALLATION TYPE

False ceiling, visible hardware

REGULATIONS

WARRANTY

5 years 50,000 h

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

6.5

PRODUCT NET WEIGHT

6

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053192214

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

65

PACKAGING WIDTH

300

PACKAGING LENGTH

1200

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

23400000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

6

PACKAGING WEIGHT UNIT

KGM