

Voice and data flat plate without dust cover for 1 element with 2 RJ45 connectors category 5e FTP white Simon K45

REF. KB095F/9



BASIC INFORMATION

DESCRIPTION

Elements of the plate for 1 and 2 RJ45 connectors model KB095F / 9 professional range of products for installations. Simon K45. High capacity for compatibilizar with other elements of the same series Simon K45. Voice and data flat plate without Dust cover with 1 element and 2 RJ45 category 5e FTP connectors with The format of snap-fit Keystone I, II, ATT ® / Avaya ® comes with insertion tool Model. It is an individual version and complex modular medium, with colours In white and shades. This made with thermoplastic components free Insulation, which, which minimizes the risk in situations of fire and smoke. Element of dimensions 45x45mm. Depth of 8,5mm, in case of voice and data plates vertical enclosures There are the need to use the 90 ° positioner (ref. K66) to guide the plate into a vertical position.

FINISH

White

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

PACKAGING CONTENTS

Voice and data flat plate without dust cover, RJ45 category 5e FTP connectors

ETIM CLASS

EC000018

REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90° positioner (ref. K66) to guide the plate into a vertical position.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

No

NUMBER OF MODULES

Half

CABLE SECTION ADMITTED (MM)

22-24 AWG wiring

FORMAT

RJ45

PLATE TYPE

Flat

RJ45 CONNECTION

With insertion tool

IP RATING

IP20

RAL

9003

CONNECTOR CHARACTERISTICS

Category 5e FTP

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

RJ45 ADAPTOR MODULE

Included in voice and data plate

RJ45 CONNECTORS

Included in voice and data plate

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

VERSION

Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-030)

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

INSTALLATION TYPE

Suitable for surface and flush mounting

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.042

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING VOLUME

3769392

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8426436032026

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0.3

UNITS CONTAINED PACKAGING

10

PACKAGING GROSS WEIGHT

0.42

UNITARY PACKAGING VOLUME
UNIT

MMQ

PACKAGING HEIGHT

118

PACKAGING NET WEIGHT

0.42

UNITARY PACKAGING GROSS
WEIGHT

0.042

PACKAGING WIDTH

121

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

264