

## PD-24 PIR+LUX surface KNX white IP54

REF. 89218736-130



### BASIC INFORMATION

#### DESCRIPTION

Presence and ambient light detector PIR. The recommended installation height is 2.8 m, with a maximum height of 4 m. It has a detection angle of 360°. The tangential detection range is 24 m and the radial detection range is 5.5 m.

The light regulation range is 2 - 800 lux. The detector configuration is done through potentiometers and KNX.

It has a TEACH operating mode. Possibility of interconnection between sensors via KNX. The control protocol is KNX. The typical consumption is 10 mA.

The power supply voltage is KNX (21 - 30 VDC). The operating temperature of the detector is: -20 - 50 °C. White finish, protection rating IP 54 and dimensions: Ø 129 x 70 mm.

5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

#### FINISH

White

#### COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

#### ETIM CLASS

EC001582

## TECHNICAL INFORMATION

### IP RATING

IP54

### POWER SUPPLY (V~)

Bus KNX (21 Vcc...32 Vcc)

### CONTROL

KNX

## INSTALLATION AND MAINTENANCE

### MINIMUM INSTALLATION HEIGHT

2

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053343050

### UNITARY PACKAGING GROSS WEIGHT

0.312

### PACKAGING LENGTH

135

### UNITARY PACKAGING HEIGHT

0

### PRODUCT NET WEIGHT

0.242

### PACKAGING MEASUREMENT UNIT

MMT

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING VOLUME

1579500

### UNITARY PACKAGING LENGTH

0

### PACKAGING EAN

8421053343050

### PACKAGING VOLUME UNIT

MMQ

### UNITARY PACKAGING MEASUREMENT UNIT

MMT

### UNITS CONTAINED PACKAGING

1

### PACKAGING GROSS WEIGHT

0.312

### UNITARY PACKAGING VOLUME

0

### PACKAGING HEIGHT

130

### PACKAGING NET WEIGHT

0.242

### UNITARY PACKAGING VOLUME UNIT

MMQ

### PACKAGING WIDTH

90

### PACKAGING WEIGHT UNIT

KGM