

Flat voice and data plate with dust cover for 1 element with 2 RJ45 category 6 UTP aluminium Simon 500 Cima

REF. 50002089-033



BASIC INFORMATION

DESCRIPTION

Did you know that the Simon 500 Cima workplace solutions system is a 50% faster installation? This is due to its click terminal connection, to its linker for sockets and its linkable centre frame, so that the use of tools is almost limited or zero. And even more tasks for ease of installation, Simon has been designed in a few kits, already configured and wired, so that only necessary to install. It has a great variety of combinations to all types of spaces and applications. From the wide range of mechanisms we find this plate for voice and data connections, flat and with dust shutter. It has 22-26 AWG of wire supported, 1 and 2 RJ45 connectors and an aluminium finish, ideal for any ambience. This plate includes an adaptor and RJ45 connectors and a snap-fit for fastening in wrappers, horizontal or vertical.

FINISH

Aluminium

PACKAGING CONTENTS

Flat voice and data plate with dust cover, 2 category 6 UTP RJ45 and installation manual

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

Yes

PLATE TYPE

Flat

CABLE SECTION ADMITTED (MM)

22-26 AWG wiring

FORMAT

RJ45

RJ45 ADAPTOR MODULE

Included in voice and data plate

RJ45 CONNECTION

With insertion tool

IP RATING

IP20

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

CONNECTOR CHARACTERISTICS

category 6 UTP

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

NUMBER OF CONNECTORS

2

VERSION

Single

RJ45 CONNECTORS

Included in voice and data plate

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

NUMBER OF MODULES

1

INSTALLATION AND MAINTENANCE

REMOVAL OF CONNECTOR

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053097878

PACKAGING VOLUME

0.052

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

20

PACKAGING VOLUME UNIT

HLT

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

80

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING GROSS WEIGHT

0.037

PACKAGING WIDTH

224

PACKAGING NET WEIGHT

0.74

PRODUCT NET WEIGHT

0.037

PACKAGING LENGTH

290

PACKAGING WEIGHT UNIT

KGM

