

Flat voice and data plate with dust cover for 1 element with 2 category 5e UTP RJ45 white Simon 500 Cima

REF. 50004089-030



BASIC INFORMATION

DESCRIPTION

Flat base plate in white colour of the Simon 500 Cima series and that is used for data and voice and has a dust cover with 1 element and 2 RJ45 category 5e UTP of Keystone I, II, ATT ® / Avaya ®. It measures 50 x 50 x 32.5 mm and allows cabling 22-26 AWG. It is a plate that has been designed according to the regulation TIA 568 C. 2 and is manufactured with metal components with thermoplastic insulation, self-extinguishing and halogen-free. This material is perfect for both in case of fire and smoke, as it prevents propagate the fire and there is a high level of toxicity. For its installation you will not need any type of adaptor, as this angled plate of the Simon 500 Cima range incorporates the clips required for fastening in horizontal and vertical enclosures, so that its installation is simple.

FINISH

White

PACKAGING CONTENTS

Flat voice and data plate with dust cover, 2 category 5e UTP RJ45 and installation manual

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

Yes

PLATE TYPE

Flat

CABLE SECTION ADMITTED (MM)

22-26 AWG wiring

FORMAT

RJ45

RAL

9003

RJ45 CONNECTION

With insertion tool

IP RATING

IP20

RJ45 ADAPTOR MODULE

Included in voice and data plate

CONNECTOR CHARACTERISTICS

Category 5e UTP

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

NUMBER OF CONNECTORS

2

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

RJ45 CONNECTORS

Included in voice and data plate

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

VERSION

Single

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

NUMBER OF MODULES

1

INSTALLATION AND MAINTENANCE

REMOVAL OF CONNECTOR

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053097922

PACKAGING VOLUME

0.052

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

20

PACKAGING VOLUME UNIT

HLT

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

80

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING GROSS
WEIGHT

0.037

PACKAGING WIDTH

224

PACKAGING NET WEIGHT

0.74

PRODUCT NET WEIGHT

0.037

PACKAGING LENGTH

290

PACKAGING WEIGHT UNIT

KGM

