

PD-20x20 PIR+LUX SR recessed DALI-2 Master white IP20

REF. 89212415-230



BASIC INFORMATION

DESCRIPTION

PIR flush-mounted presence and brightness detector. The recommended installation height is 2.8 m, with a maximum height of 10 m. It has a detection angle of 360° and an opening angle of 180°. The tangential detection range is 20 x 20 m and the radial detection range is 8 x 8 m.

The brightness regulation range is 10 - 1000 lux and the timing range is 5 s - 60 min. The detector configuration is performed via remote control.

It has a TEACH operating mode. Possibility of interconnection between sensors. The control protocol is DALI-2 Master. The number of dimmable luminaires through the DALI bus is 64 (3 groups).

The power supply voltage is 220 - 240 VAC. The operating temperature of the detector is: 0 - 40 °C.

White finish, protection rating IP 20 and dimensions: 120 x 120 x 119 mm.

5-year warranty

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

Yes

ETIM CLASS

EC000133

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

POWER SUPPLY (V~)

220/240 V~

CONTROL

DALI2 Master

IP RATING

IP20

RAL

9003

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2.5

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053342411

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.49

PRODUCT NET WEIGHT

0.364

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053342411

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

160

PACKAGING WIDTH

115

PACKAGING LENGTH

205

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

3772000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.49

PACKAGING NET WEIGHT

0.364

PACKAGING WEIGHT UNIT

KGM