Hinged cover for adjustable floor box or service cover in concrete or raised floor for 12 elements graphite Simon 500 Cima

REF. **RSF006/14**



BASIC INFORMATION

DESCRIPTION

With a perfect in graphite finishes, our hinged cover 12 elements of the Simon 500 Cima series can be used for adjustable floor box, register in concrete or even for our raised floor, and that is that this piece of 200x292x15 mm, it is made of metal components with thermoplastic insulation coated self-extinguishing, halogen-free in order to ensure that, in case of fire, the fire is not propagate, in addition to a toxicity very low if had any smoke. We can ensure that the commitment Simon is to offer the maximum guarantee in its products through its commitment to innovation, and that is that the collection Simon 500 Cima offers the best solutions for those who are looking for the mechanisms functional to get make your home a place much safer. You the piences more, and confident in the most specialized brand.

FINISH

Graphite

PACKAGING CONTENTS

Hinged cover

MATERIAL

Plastic

ETIM CLASS

EC001903

REMARKS

The adjustable floor boxes include the hinged cover. Only necessary to order it as a replacement part in the event of breakage or loss.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS
No

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS
Yes, thanks to the inclusion of protective foam

AVAILABLE IN
2, 4, 6, 8 and 12 elements

DIELECTRIC STRENGTH
No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)
+90 °C

HEAT RESISTANCE (°C)
+125°C (according rule IEC 60695-10-2)

INSULATION RESISTANCE (V-MΩ)
>5 MOhms at 500V

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60 °C

NUMBER OF MODULES
12 modules

RAL
7021

VERSION
12 elements

INSTALLATION AND MAINTENANCE

TYPE OF FASTENING
Via coupling pin supplied on the cover

INSTALLATION DIRECTION
Horizontal and vertical, in accordance with the installation of the floor box or service cover

INSTALLATION TYPE
In raised or concrete floor with adjustable floor boxes or service covers

REGULATIONS

REGULATIONS
UNE-EN 60.670-23

LOGISTICS INFORMATION

UNITARY EAN CODE
8426436056251

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING MEASUREMENT UNIT
MMT

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
1.32

PRODUCT NET WEIGHT
1.32

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436056251

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
20

PACKAGING WIDTH
350

PACKAGING LENGTH
250

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
1.75

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
1.32

PACKAGING WEIGHT UNIT
KGM