

Voice and data flat plate without dust cover for 1 element with 2 RJ45 connectors category 6 UTP white Simon K45

REF. KB096U/9



BASIC INFORMATION

DESCRIPTION

Between connectors and plates for voice and data connections of Simon is available this flat base plate of voice and data. Does not include dust shutter and has a single element and 2 RJ45 category 6 UTP. It has a beautiful finish is white in colour and is part of the series Simon K45. It can be installed flush mounted or surface-mounted. The snap-fit is performed by Keystone I, II, ATT, Avaya. The connection of this plate in individual version and half element is made by means of insertion tool. It is possible to find the product both for one as for two RJ45 connectors. To combine the plate in vertical enclosures, such as columns holder or Teleblock, channels, mechanism, you have to use the 90 ° positioner Simon reference (: K66). The dimensions of the plate are 45 x 45 millimetres and a depth of 8.5 millimetres. It is manufactured from high quality materials, they bet for the metal components with thermoplastic insulation and halogen-free. This means that support very variable temperature, that arrive at the + 60 degrees centigrade maximum.

FINISH

White

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

PACKAGING CONTENTS

Flat voice and data plate without dust cover, RJ45 category 6 UTP connectors and installation manual

ETIM CLASS

EC000018

REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90° positioner (ref. K66) to guide the plate into a vertical position.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

No

NUMBER OF MODULES

Half

CABLE SECTION ADMITTED (MM)

22-26 AWG wiring

FORMAT

RJ45

PLATE TYPE

Flat

RJ45 CONNECTION

With insertion tool

IP RATING

IP20

RAL

9003

CONNECTOR CHARACTERISTICS

Category 6 UTP

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

RJ45 ADAPTOR MODULE

Included in voice and data plate

RJ45 CONNECTORS

Included in voice and data plate

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

VERSION

Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-030)

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

INSTALLATION TYPE

Suitable for surface and flush mounting

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.033

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING VOLUME

1472064

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8426436032040

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0.3

UNITS CONTAINED PACKAGING

10

PACKAGING GROSS WEIGHT

0.33

UNITARY PACKAGING VOLUME
UNIT

MMQ

PACKAGING HEIGHT

88

PACKAGING NET WEIGHT

0.33

UNITARY PACKAGING GROSS
WEIGHT

0.033

PACKAGING WIDTH

123

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

136