

Modular luminaire 726 60x60 Low Glare WW DALI

REF. 72660333-683



BASIC INFORMATION

DESCRIPTION

Luminaire Modular 726 60 x 60 LowGlare. It is a product designed by the indoor lighting brand Simon. This luminaire has lights led in warm colour (WW) and its electrical control is DALI. It is presented in a perfect finish in aluminium colour, which makes it ideal for position, place in any space, achieving a indoor lighting of the highest quality. The modular luminaire Simon is category B and has microprismatic optics. The temperature of the colour of the product is of 3000 K and has a total of 2900 lumens, for a power of his 39 W power supply is 100-240 V and its frequency is 50 / 60 Hz. The dimensions of the luminaire are 595 millimetres and must be installed in a false ceiling with the hardware to the total. The weight of the product is of 2,6 kilos. It is, therefore, a very liviana luminaire and high usability.

DIFFUSER MATERIAL

PMMA

PACKAGING CONTENTS

1 unit

APPLICATION

General lighting

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DRIVER INCLUDED

Yes

LUMENS (LM)

2900 lm

IP RATING

IP20

ELECTRICAL CLASS

Tipo 2

LUMENS/W

2900 lm/39W

OPERATING TEMPERATURE RANGE (°C)

-15 - 40 °C

INTEGRATED POWER SUPPLY

No

OPTICS

Microprismatic

POWER SUPPLY (V~)

100/240 V~

L70 (°C)

30,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempted category

COLOR TEMPERATURE (K)

3000 K

LIGHT BEAM APERTURE ANGLE (°)

90°

POWER (W)

39 W

CONTROL

DALI

COLOR TYPE

WW

SERVICE LIFE

30.000 h


CRI

80

LIGHTING EFFICIENCY (LM/W)

74 lm/W

CHROMATICS CRI ICONS



INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Plaster ceiling, surface mount, flush mount, concealed profile and suspended

MINIMUM INSTALLATION HEIGHT

250

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

INSTALLATION TYPE

False ceiling, visible hardware

REGULATIONS

WARRANTY

3 years 30,000 h

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT	UNITARY PACKAGING WEIGHT UNIT	PACKAGING MEASUREMENT UNIT
0	KGM	MMT
UNITARY PACKAGING WIDTH	PACKAGING EAN	PACKAGING VOLUME
0	8421053193969	25918750
UNITARY PACKAGING LENGTH	UNITS CONTAINED PACKAGING	PACKAGING VOLUME UNIT
0	1	MMQ
UNITARY PACKAGING VOLUME	PACKAGING HEIGHT	PACKAGING GROSS WEIGHT
0	55	3
UNITARY PACKAGING GROSS WEIGHT	PACKAGING WIDTH	PACKAGING NET WEIGHT
3	725	2.1
PRODUCT NET WEIGHT	PACKAGING LENGTH	PACKAGING WEIGHT UNIT
2.1	650	KGM