

Front face kit for 2 elements with 1 2P socket, 1 single R / TV + SAT socket with 1 RJ45 category 6 UTP connector gloss black Simon 100

REF. 10020226-138



BASIC INFORMATION

FINISH

Gloss black

ETIM CLASS

EC000007

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

TYPE OF MECHANISM

Momentary switch / Insert button

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Suitable for flush mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1

2P socket: Connection (1 click®)

TYPE OF TERMINAL CONNECTION - FUNCTION 2

R-TV+SAT: Screw

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2014/30/UE EMC + Directive 2011/65/UE RoHS + EN 50083-2:2012*4 + EN 50581:2012 + IEC 60603-7-4:2010*5 + IEC 60884-1 Ed. 3.2*1

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053232378

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053232378

PACKAGING VOLUME

329406

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

25.3

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

84

PACKAGING NET WEIGHT

0.083

UNITARY PACKAGING GROSS
WEIGHT

0.083

PACKAGING LENGTH

155

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.083