

Cover and trim frame for Teleblock telescopic profile black Simon K45

REF. KTLA1/14



BASIC INFORMATION

DESCRIPTION

The Cover and trim frame for Teleblock telescopic profile in black finish of the series Simon K45 conjugate perfectly innovative design and maximum quality at the best price, making it one of the most appealing that we can find in the market today, its dimensions are Ø 127 mm and is available in black and matt chromed, although Simon offers the possibility of supply in other finishes always order. The material with which it has been manufactured contains self-extinguishing thermoplastic and halogen-free; guarantees no flame propagation in case of fire and the low toxicity in case of smoke, being an element suitable to be flush mounted in furniture. The security that gives the electrical installations and the ease of cleaning its structure and keep it as the first day, is another of its advantages.

FINISH

Black

MATERIAL

Plastic

COMPATIBILITY

Teleblock with manual elevation from the Simon K45 range.

PACKAGING CONTENTS

Cover, trim frame, rubber gland and installation manual.

ETIM CLASS

EC002649

REMARKS

Other finishes may be supplied (on request).

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the silicone gasket on the cover that prevents the entry of external elements when there are no connections. Yes, thanks to the silicone gasket on the cover that prevents the entry of external elements when there are no connections.

AVAILABLE IN

Available in black and matt chrome

DIELECTRIC STRENGTH

Without perforation or contournement with 2000 V at 50Hz during 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

INSULATION RESISTANCE (V-MΩ)

>5 MOhm at 500 V

IP RATING

IP4X

KIT AVAILABILITY

No

LINKABLE

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

RAL

7021

INSTALLATION AND MAINTENANCE

REMOVAL OF COVER

Only with tool

EXTINGUISHING (°C)

+850 °C (according to standard IEC 60670)

TYPE OF FASTENING

By the threading at 45° to the cover on the top closure supplied with the Simon Teleblock K45 telescopic profile.

REMOVAL OF THE FRAME

Only with tool

INSTALLATION TYPE

Suitable for embedding in furniture.

SECURING POSSIBILITIES

Its design allows for cabling and wiring, lowering the telescopic profile, integrating into the furniture, keeping the connections active and serving as a cable guide.

MOUNTING WITHOUT ACCESSORIES

The cover and decorative frame are supplied with all necessary installation materials, without the need for additional references for attachment.

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60670-1:2005

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436051621

PRODUCT NET WEIGHT

0.151

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

453024

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8426436051621

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.151

UNITARY PACKAGING VOLUME

453024

PACKAGING HEIGHT

132

PACKAGING NET WEIGHT

0.151

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

26

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

0.151

PACKAGING LENGTH

132