

Customisable flush-mounted in the desk kit with dual opening cover and fins, 4 German socket outlets and 4 empty elements aluminium Simon 400

REF. 47402000-133



BASIC INFORMATION

DESCRIPTION

More and more professionals that they bet for the kit is part of the table customizable with cover with two opening and fins and empty four elements finished in aluminium of the series Simon 400. With 4 SCHUKOS sockets for standard current circuit, has a current of 16 A and a voltage of 250 V ~, being compatible with the rest of the functions of the range Simon 400. Suitable to be flush mounted in furniture, this kit has a connector figure Wieland ® gst18i with 3 poles male in-line with patch cord of 22 cm, insulation resistance > 5 M Ω at 500 V and dielectric strength with no holes or contours with 2000 V at 50H during 1 minute. It has been designed with enclosure painted steel, profile in anodised aluminium, covers and fastenings in self-extinguishing thermoplastic and halogen-free, a component that guarantees no flame propagation in case of fire and low toxicity in the event of smoke generation.

FINISH

Aluminium

MATERIAL

Metal

COMPATIBILITY

Functions of the Simon 400 range, combinable with the Simon Electric Cabling range.

PACKAGING CONTENTS

Pre-wired profiles, enclosure, fastening claws, 3-pole T-branching with 1 male input and 2 female outputs and installation manual.

REMARKS

To complete the product installation combine it with the Simon 400 functions (refs. 400XXXXX-03X).

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

FORMAT

Schuko

NOMINAL VOLTAGE (V~)

250 V~

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

No

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

TYPE OF POWER SUPPLY CONNECTOR

Wieland  GST 18i male 3-pole overhead connector with 22 cm patch cord

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the included protective cover and cable outlet with metal fin

INSULATION RESISTANCE (V-MΩ)

>5 MΩ at 500 V

RAL

9006

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

IP RATING

IP30

NUMBER OF REAR ENTRANCES

4

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60  C

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

RECESS DIMENSION (MM)

228 x 175 mm (± 2mm)

NUMBER OF POSSIBLE ELEMENTS

4

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 at +60  C

NUMBER OF SOCKETS

4 sockets for standard current circuit

VERSION

8 elements

INSTALLATION AND MAINTENANCE

CABLING ACCESS

With metal fin

CLAW RANGE OF OPERATION (MM)

Between 20 and 40 mm

REMOVAL OF COMPONENTS

NUMBER OF COVER OPENING POSITIONS

2

EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

TYPE OF FASTENING

By lateral tightening of claws provided with the enclosure.

Optional possibility to fasten the enclosure with screws through the provided holes in the sides of the enclosure chassis.

REMOVAL OF THE FRAME

Only with tool

INSTALLATION TYPE

Suitable for recessed mount in furniture.

OPENING ORIENTATION

At 45° and 135°

REMOVAL OF THE PLATE

Only with tool

SECURING POSSIBILITIES

Using supplied claws or screws in the available holes

MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS

Directiva 2014/35/UE LVD; Directiva 2011/65/UE RoHS; EN 50581:2012; EN 60670-1:2005; EN 60670-1:2005 A1:2013; IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053197332

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

2.45

PRODUCT NET WEIGHT

2.45

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053197332

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

370

PACKAGING WIDTH

135

PACKAGING LENGTH

200

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

9990000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

2.45

PACKAGING WEIGHT UNIT

KGM