Module Downlight LED Simon 704 2700K Spot DALI Blanco

REF. **70400330-282**



BASIC INFORMATION

APPLICATION

Accent lighting,General lighting

ETIM CLASS

EC000996

TECHNICAL INFORMATION

FREQUENCY
50 - 60 Hz

IP RATING
IP20

OPERATING TEMPERATURE RANGE (ºC)
-15 to 35ºC

POWER SUPPLY (V~)
220/240 V~

COLOR TEMPERATURE (K)
2700K

CONTROL
DALI

CRI
80

LIGHT BEAM APERTURE ANGLE (°)
20º

LIGHTING EFFICIENCY (LM/W)
85 lm/W

LUMENS (LM)
1030 lm

LUMENS/W
1030 lm/12W

OPTICS
Spot

SERVICE LIFE
30.000 h

CHROMATICS CRI ICONS



REGULATIONS

WARRANTY
3 years 30.000 h

REGULATIONS
Dir. 2014/30/UE EMC | Dir. 2014/35/UE LVD | Dir. 2009/125/EC ErP (Reg. UE 2019/2015) | Dir. 2009/125/EC ErP (Reg. UE 2019/2020) | Dir. 2011/65/UE RoHS + post. mod. | EN IEC 55015:2019 + A11:2020 | EN IEC 60598-2-1:2021 | EN IEC 61547:2023 | EN 60598-2-2:2012 | EN 61000-3-3:2013 + A1:2019 + A2:2021 | EN 62493:2015 | EN IEC 63000:2018 | EN 62717:2017 + A2:2019

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053225530

UNITARY PACKAGING HEIGHT
165

UNITARY PACKAGING WIDTH
85

UNITARY PACKAGING LENGTH
118

UNITARY PACKAGING MEASUREMENT UNIT
MMT

UNITARY PACKAGING VOLUME
1.655

UNITARY PACKAGING VOLUME UNIT
DMQ

UNITARY PACKAGING GROSS WEIGHT
0.368

PRODUCT NET WEIGHT
0.298

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053225530

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
165

PACKAGING WIDTH
85

PACKAGING LENGTH
118

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
1654950

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.368

PACKAGING NET WEIGHT
0.298

PACKAGING WEIGHT UNIT
KGM