

Angled voice and data plate with dust cover for 1 element with 1 category 5e UTP RJ45 graphite Simon 500 Cima

REF. 50004081-038



BASIC INFORMATION

DESCRIPTION

Angled plate for voice and data of the Simon 500 Cima series and available in graphite colour, it is a plate with dust cover with 1 element and 1 RJ45 category 5e UTP of Keystone I, II, ATT ® / Avaya ®. To install it, you will not need any adapter, as the plate includes the clips required for fastening in vertical and horizontal enclosures. It measures 50 x 50 x 42,5 mm and has been manufactured with metal components with self-extinguishing, halogen-free thermoplastic insulation. This material guarantees that, in case of fire, are not propagate the fire and, in the event of smoke generation, has a low level of toxicity. Also, has been designed in accordance with the regulation TIA 568 C. 2. It is a perfect plate to install in public places with a temperature between -5 and the most of 60 ° C, making it perfect for any type of climatology. Its cleaning is quite simple, just use a soft, dry cloth.

FINISH

Graphite

PACKAGING CONTENTS

Angled voice and data plate with dust cover, category 5e UTP RJ45 connector and installation manual

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

Yes

NUMBER OF MODULES

1

CABLE SECTION ADMITTED (MM)

22-26 AWG wiring

DUST SHUTTER

Yes

PLATE TYPE

Angled

AVAILABLE IN

Plate for 1 and 2 RJ45

FORMAT

RJ45

RAL

7021

RJ45 CONNECTION

With insertion tool

IP RATING

IP20

RJ45 ADAPTOR MODULE

Included in voice and data plate

CONNECTOR CHARACTERISTICS

Category 5e UTP

KIT AVAILABILITY

No

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

NUMBER OF CONNECTORS

1

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

RJ45 CONNECTORS

Included in voice and data plate

VERSION

Single

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

INSTALLATION AND MAINTENANCE

REMOVAL OF CONNECTOR

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

26

UNITARY PACKAGING GROSS WEIGHT

0.058

PACKAGING LENGTH

86

UNITARY PACKAGING WIDTH

58

PRODUCT NET WEIGHT

0.058

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING LENGTH

86

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

0.052

UNITARY PACKAGING MEASUREMENT UNIT

MMT

PACKAGING EAN

8421053097809

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

129688

UNITS CONTAINED PACKAGING

20

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING HEIGHT

26

PACKAGING NET WEIGHT

1.16

PACKAGING WIDTH

58

PACKAGING WEIGHT UNIT

KGM

