

Luminaire de pared L 20 for E27 with detector 10m 180° PIR+LUX IP44 3Y

REF. 89195000-600



BASIC INFORMATION

DESCRIPTION

Wall-mounted HF detector light. The power is max 60 W. The maximum installation height is 4m and the installation is on the wall (surface). The detection range is 10m and the detection angle is 180 °. The brightness regulation range is 2 - 2000 lux and the timing range is 8 s - 35 min. The luminaire configuration is done through potentiometers. The power supply voltage is 220 - 240 VAC. The operating temperature is: -20 - 40 °C. Protection grade IP 44 and IK 07 and dimensions: 230 x 250 x 85 mm. 3-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

Aluminium

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

IP RATING

IP44

IK CLASSIFICATION

07

POWER SUPPLY (V~)

220/240 V~

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053370346

UNITARY PACKAGING GROSS WEIGHT

1.5

PACKAGING LENGTH

30

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.7

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

2325323

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053370346

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

1.5

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

25

PACKAGING NET WEIGHT

0.7

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

13.5

PACKAGING WEIGHT UNIT

KGM