

MD-23x6 Hallway PIR+LUX recessed box DALI-2 Input round white IP20

REF. 89205325-130



BASIC INFORMATION

DESCRIPTION

PIR flush-mounted motion and light detector. The recommended installation height is 2.8 m, with a maximum height of 5 m. It has a detection angle of 360° and an opening angle of 45°. The tangential detection range is 23 x 6 m and the radial detection range is 12 x 6 m. The luminosity regulation range is 2 - 1000 lux. The detector configuration is done via DALI. Possibility of interconnection between sensors through DALI. The control protocol is DALI-2 Input. The typical consumption is 5 mA. The power supply voltage is DALI (12 - 20.5 VDC). The operating temperature of the detector is: -20 - 50 °C. White finish, IP 20 protection degree, and dimensions: Ø 124 x 78 mm. 5-year warranty

For more product information, visit STEINEL website by clicking [here](#)

FINISH
White

**COMPATIBLE WITH MECHANICAL
PUSH BUTTON**
No

ETIM CLASS
EC001582

TECHNICAL INFORMATION

IP RATING

IP20

RAL

9003

POWER SUPPLY (V~)

DALI bus (12 Vdc – 20,5 Vdc)

CONTROL

DALI2 Slave

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2.5

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053341889

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.227

PRODUCT NET WEIGHT

0.137

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053341889

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

90

PACKAGING WIDTH

124

PACKAGING LENGTH

160

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

1785600

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.227

PACKAGING NET WEIGHT

0.137

PACKAGING WEIGHT UNIT

KGM