Adjustable floor box with 6 elements for installation in Simon K45 graphite raised floor

REF. **KF610/14**



BASIC INFORMATION

DESCRIPTION

In the recessed raised floor category, you'll find this adjustable floor box for 6 elements, in graphite. The product measures 226 x 187 x 92 mm and has been manufactured in full compliance with regulations. It contains metal elements with halogen-free insulation, which is self-extinguishing. This means it ensures there is no flame propagation in case of fire, as well as low toxicity in case of smoke. After installation, this floor box can be combined with a flush-mount trim cover if the same finish has not been installed on the floor itself. The mechanism belongs to the Simon K45 series, a collection that offers a fast and versatile workplace solutions system. To maintain the piece, you can use a soft, dry cloth.

FINISH

Graphite

MATERIAL

Various

COMPATIBILITY

With Simon K45 mechanisms (no adaptor required)

PACKAGING CONTENTS

Floor box, metal partition wall, ground connection cable, screws and installation manual

ETIM CLASS

EC000024

REMARKS

Once the product has been configured and installed, as an option, it may be combined with flush-mount trim cover (Art. No. 52053103-038) in cases where the same floor finish is not installed.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS
Yes, thanks to the inclusion of protective foam in the wire outlet

AVAILABLE IN
2, 4, 6, 8 and 12 elements

NUMBER OF CLAMP-HOLDER HOLES
8

DIELECTRIC STRENGTH
No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)
+90° C

ELECTROMAGNETIC IMMUNITY FOR VDM WIRING
Secured by installing the metal partition wall supplied with the box into the housings fitted for this purpose.

HEAT RESISTANCE (°C)
+125 °C (in accordance with standard IEC 60695-10-2)

IK CLASSIFICATION
08

INSULATION RESISTANCE (V-MΩ)
>5 MΩ a 500 V

IP RATING
IP4X

KIT AVAILABILITY
No

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MAXIMUM LOAD (KG)
1700kg

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 a +60° C

NUMBER OF MODULES
6 modules

RAL
7021

RECESS DIMENSION (MM)
170 x 210 mm

NUMBER OF SIDE ENTRANCES
12

VERSION
6 elements

INSTALLATION AND MAINTENANCE

CLAW RANGE OF OPERATION (MM)
Between 14 and 54 mm

REMOVAL OF COMPONENTS
Only with tool

NUMBER OF COVER OPENING POSITIONS
2

REMOVAL OF COVER
Only with tool

EXTINGUISHING (ºC)
+850 ºC / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

TYPE OF FASTENING
By fastening the claws on the floor box into the holes in the raised floor tile (supplied in the floor box)

REMOVAL OF THE FRAME
Only with tool

INSTALLATION DIRECTION
Horizontal

INSTALLATION TYPE
Especially designed to be installed in raised floors

REGULATIONS

REGULATIONS
2006/95/CE Directive + UNE-EN 60,670

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053125298

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
1.4

PRODUCT NET WEIGHT
1.4

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053125298

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
95

PACKAGING WIDTH
186

PACKAGING LENGTH
226

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
3993420

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
1.4

PACKAGING NET WEIGHT
1.4

PACKAGING WEIGHT UNIT
KGM