

Downlight 725.26 NW Comfort DALI

REF. 72526330-884



BASIC INFORMATION

APPLICATION

Accent lighting, General lighting

PACKAGING CONTENTS

1 unit

ETIM CLASS

EC001744

TECHNICAL INFORMATION

IP RATING

IP44

DRIVER INCLUDED

Yes

LUMENS (LM)

1400 lm

OPERATING TEMPERATURE RANGE (°C)

-10 - 35 °C

L70 (°C)

30,000 h

LUMENS/W

1400 lm/14W

COLOR TEMPERATURE (K)

4000 K

LIGHT BEAM APERTURE ANGLE (°)

120°

OPTICS

General

CONTROL

DALI

COLOR TYPE

NW

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

CRI

80

LIGHTING EFFICIENCY (LM/W)

100 lm/W

POWER (W)

14 W

CHROMATICS CRI ICONS

CRI
80

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Surface-mounted

INSTALLATION TYPE

Flush-mounted

REGULATIONS

WARRANTY

3 years

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053089767

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.657

PRODUCT NET WEIGHT

0.499

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053089767

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

100

PACKAGING WIDTH

185

PACKAGING LENGTH

175

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

3237500

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.657

PACKAGING NET WEIGHT

0.499

PACKAGING WEIGHT UNIT

KGM