

Voice and data flat plate without dust cover for 1 element with 2 RJ45 connectors category 5e UTP white Simon K45

REF. KB095U/9



BASIC INFORMATION

DESCRIPTION

Model of plate for series KB095U / 9 belonging to the professional Range of products SimonK45, easy combination with other types of elements Installation and assembly. It is a aplaca voice and Data of flat format, without dust cover with 1 element and for two connectors Category 5e UTP RJ45 with snap-fit Keystone I, II, ATT ® / Avaya ®, integrated Insertion tool. Individual version of colour and finishes White in colour, it has metallic components with halogen-free Self-extinguishing halogen-free thermoplastic that guarantees no flame propagation In case of fire and the low toxicity, optimising a Maximum security professional certified. For models of plate of voice and Data in vertical enclosures, it is necessary to the combination with element 90 ° positioner (Ref. K66) to guide the plate into a vertical position. Measures 45x45mm and a depth of 8,5mm, being an element of great versatility For different environments.

FINISH

White

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

PACKAGING CONTENTS

Flat voice and data plate without dust cover, RJ45 category 5e UTP connectors and installation manual

ETIM CLASS

EC000018

REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90° positioner (ref. K66) to guide the plate into a vertical position.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

No

NUMBER OF MODULES

Half

CABLE SECTION ADMITTED (MM)

22-26 AWG wiring

DUST SHUTTER

No

PLATE TYPE

Flat

AVAILABLE IN

Plate with 1 and 2 RJ45 connectors

FORMAT

RJ45

RAL

9003

RJ45 CONNECTION

With insertion tool

IP RATING

IP20

RJ45 ADAPTOR MODULE

Included in voice and data plate

CONNECTOR CHARACTERISTICS

Category 5e UTP

KIT AVAILABILITY

No

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

RJ45 CONNECTORS

Included in voice and data plate

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

VERSION

Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-030)

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

INSTALLATION TYPE

Suitable for surface and flush mounting

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.03

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

1472064

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8426436032033

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0.3

UNITS CONTAINED PACKAGING

10

PACKAGING GROSS WEIGHT

0.3

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING HEIGHT

88

PACKAGING NET WEIGHT

0.3

UNITARY PACKAGING GROSS WEIGHT

0.03

PACKAGING WIDTH

123

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

136