Module for 1 RJ45 R&M® in angled voice and data plates

REF. **MD54**



BASIC INFORMATION

DESCRIPTION

It belongs to the Simon 500 Cima series, and is a product is ideal for connector, 1 R & M ® RJ45 in angled voice and data plates of the same series of Simon products. The module is installed in a very simple and measures 32 x 20 millimetres and 10 millimetres of depth. Simon uses the best materials in the manufacture of their products, always with the aim of convert it into highly functional to technical level, as well as durable over time. In this case, the module is manufactured with halogen-free thermoplastic material, the latest in the market technology. This material is highly resistant and provides an extra hardness the product, so this is susceptible to withstand challenges external as knocks or scratches without visible due to its good operation. In addition, it can withstand temperatures also high or very low between -5 and 60 degrees centigrade. To be thermoplastic insulation, also contributes to the no-propagation of the spread in case of fire and reduces the toxicity of smoke, if this is producing. For this reason, the module, and the set in general it is highly secure.

COMPATIBILITY

Simon 500 Cima and Simon K45 angled voice and data plates

PACKAGING CONTENTS

MD Module for 1 RJ45

ETIM CLASS

EC002948

REMARKS

The MD Module can only be combined with angled voice and data plates (flat voice and data plates include the MD Module on the plate itself).

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

COMPATIBLE WITH CONNECTORS
Classic series Cat5e (R925371, R925370), Star Cat6 series (R302373, R302372) and Advanced Cat6A series (R509500, R509504) from R&M® (Reichle de Massari®).

RJ45 CONNECTORS
Not included in the MD Module

MAX TEMP DURING CONSTRUCTION WORK (°C)
+60 °C

FORMAT
RJ45

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60 °C

SNAP-FIT RJ45 PLATES
RJ45 R&M® connectors

SNAP-FIT TYPE
RJ45 R&M® connectors

INSTALLATION AND MAINTENANCE

INSTALLATION DIRECTION
Vertical, corresponding with the MD Module fastening slots

INSTALLATION TYPE
Fixing by direct snap-fit, no tools needed.

REGULATIONS

REGULATIONS
Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0.3

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.002

PRODUCT NET WEIGHT
0.002

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436037885

UNITS CONTAINED PACKAGING
50

PACKAGING HEIGHT
72

PACKAGING WIDTH
72

PACKAGING LENGTH
105

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
544320

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.1

PACKAGING NET WEIGHT
0.1

PACKAGING WEIGHT UNIT
KGM