

PD-15 True Presence HF+LUX BT Mesh surface DALI-2 Input white IP54

REF. 89210334-230



BASIC INFORMATION

DESCRIPTION

Presence and light surface detector. The recommended installation height is 2.8 m, with the minimum height being 2.5 m and the maximum height 12 m. It has a detection angle of 360 ° and an opening angle of 160°. The tangential detection range is 15 m and the radial detection range is 15 m. The presence detection range is 15 m and the real presence detection range is 9 m.

The light measurement range is 2 - 1000 lux. The detector configuration is done through the DALI bus. Possibility of interconnection between sensors via DALI. The control protocol is DALI-2 Input. The typical consumption is 2 mA.

The power supply voltage is 220 - 240 VAC. The operating temperature of the detector is: -20 - 50 °C.

White finish, IP 20 protection grade, and dimensions: 123 x 123 x 45 mm.

5-year warranty.

For more product information visit the STEINEL website by clicking [here](#).

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

TECHNICAL INFORMATION

IP RATING

IP54

POWER SUPPLY (V~)

DALI bus (12 Vdc – 20,5 Vdc)

CONTROL

DALI2 Slave

OPERATING TEMPERATURE RANGE (°C)

-20...+50

RAL

9003

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2 m

INSTALLATION TYPE

Surface mounting

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053439425

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.376

PRODUCT NET WEIGHT

0.27

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053439425

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

161

PACKAGING WIDTH

101

PACKAGING LENGTH

143

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2325323

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.376

PACKAGING NET WEIGHT

0.27

PACKAGING WEIGHT UNIT

KGM