

PD-24 PIR+LUX recessed DALI-2 Input black IP20

REF. 89218316-138



BASIC INFORMATION

DESCRIPTION

Presence and brightness detector for flush mounting PIR. The recommended installation height is 2.8 m, with a maximum height of 4 m. It has a detection angle of 360 °. The tangential detection range is 24 m and the radial detection range is 5.5 m.

The brightness regulation range is 2 - 1000 lux. The detector configuration is done via DALI.

It features a TEACH operating mode. Possibility of interconnection between sensors via DALI. The control protocol is DALI-2 Input. The typical consumption is 12 mA.

The power supply voltage is DALI (12 - 20.5 VDC). The operating temperature of the detector is: -20 - 50 °C.

Black finish, IP 20 protection rating, and dimensions: Ø 109 x 114 mm.

5-year warranty

For more product information, visit STEINEL website by clicking [here](#)

FINISH

Black

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

ETIM CLASS

EC001582

TECHNICAL INFORMATION

IP RATING

IP20

POWER SUPPLY (V~)

DALI bus (12 Vdc – 20,5 Vdc)

CONTROL

DALI2 Slave

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053342886

UNITARY PACKAGING GROSS WEIGHT

0.336

PACKAGING LENGTH

140

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.196

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

2744000

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053342886

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.336

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

140

PACKAGING NET WEIGHT

0.196

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

140

PACKAGING WEIGHT UNIT

KGM