

Modular Luminaire 720 Advance M4 60x60 NW DALI

REF. 72060340-884



BASIC INFORMATION

DESCRIPTION

Luminaire Modular Advance M4 60x60, of the series of Simon 720 modular luminaires. It is category B and the colour of the light is neutral (NW). With a translucent optics and colour temperature of 400 k, offers a high efficiency in its use. It is perfect for the indoor lighting, as well as to give light to transit areas. This luminaire Simon has 4100 lumens and a power of 34 W you need a power supply of 230 V and has a frequency of 50 / 60 Hz. The electric control of the apparatus shall be performed by DALI and withstands temperatures of up to 40 degrees centigrade. The dimensions of this luminaire Simon are 595 x 595 x 60 millimetres and has a weight of 4,9 kilos. Its finish is white in colour, to be able to be installed in different spaces, without clash in absolute optimum. Its installation is done in false ceiling with hardware.

DIFFUSER MATERIAL

PMMA

PACKAGING CONTENTS

1 unit

APPLICATION

General lighting

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DRIVER INCLUDED

Yes

LIGHTING EFFICIENCY (LM/W)

146 lm/W

IP RATING

IP44

ELECTRICAL CLASS

Tipo 2

LUMENS (LM)

4100 lm

OPERATING TEMPERATURE RANGE (°C)

40 °C maximum

INTEGRATED POWER SUPPLY

Yes

LUMENS/W

4100 lm/28W

POWER SUPPLY (V~)

230 V~

L70 (°C)

100,000 h at 25 °C

OPTICS

Translucent

COLOR TEMPERATURE (K)

4000 K

L90 (°C)

40,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempted category

CONTROL

DALI

LIGHT BEAM APERTURE ANGLE (°)

120°

POWER (W)

28 W

CRI

82

COLOR TYPE

NW

SERVICE LIFE

50.000 h

CHROMATICS CRI ICONS

CRI
82

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Plaster ceiling, surface mount, concealed or semi-concealed profile.

MINIMUM INSTALLATION HEIGHT

120

INSTALLATION TYPE

False ceiling, visible hardware

TYPE OF TERMINAL

CONNECTION - FUNCTION 1

Quick connector

REGULATIONS

WARRANTY

5 years 50,000 h

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053124734

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

5.62

PRODUCT NET WEIGHT

5

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053124734

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

65

PACKAGING WIDTH

600

PACKAGING LENGTH

600

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

0.234

PACKAGING VOLUME UNIT

HLT

PACKAGING GROSS WEIGHT

5.62

PACKAGING NET WEIGHT

5

PACKAGING WEIGHT UNIT

KGM