

Bell unipolar push button 10A 127-220V with screw terminal connection aluminum Simon 25 Plus

REF. 25150-33



BASIC INFORMATION

FINISH

Aluminium

TECHNICAL INFORMATION

CABLE SECTION ADMITTED (MM)

3,3 mm

CURRENT (A)

10 A

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VOLTAGE (V~)

127/220 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY
(MM)

11

TYPE OF TERMINAL
CONNECTION - FUNCTION 1

Fast

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

22.2

UNITARY PACKAGING GROSS
WEIGHT

23

PACKAGING LENGTH

224

UNITARY PACKAGING WIDTH

40.5

PRODUCT NET WEIGHT

23

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING LENGTH

41.2

UNITARY PACKAGING WEIGHT
UNIT

GRM

PACKAGING VOLUME

0.857

UNITARY PACKAGING
MEASUREMENT UNIT

MMT

PACKAGING EAN

7506207331471

PACKAGING VOLUME UNIT

DMQ

UNITARY PACKAGING VOLUME

0.037

UNITS CONTAINED PACKAGING

20

PACKAGING GROSS WEIGHT

0.46

UNITARY PACKAGING VOLUME
UNIT

DMQ

PACKAGING HEIGHT

45

PACKAGING NET WEIGHT

460

PACKAGING WIDTH

85

PACKAGING WEIGHT UNIT

KGM