

## LedFlex 810.35 3000 K IP65

REF. 81035100-983



### BASIC INFORMATION

#### APPLICATION

General lighting,Indoor decorative lighting

#### PACKAGING CONTENTS

1 unit (5m)

#### ETIM CLASS

EC002706

## TECHNICAL INFORMATION

### IP RATING

IP65

### DRIVER INCLUDED

No

### LUMENS (LM)

4800 lm

### OPERATING TEMPERATURE RANGE (°C)

-20 - 40 °C

### L70 (°C)

30,000 h

### LUMENS/W

4800 lm/48W

### COLOR TEMPERATURE (K)

3000 K

### LIGHT BEAM APERTURE ANGLE (°)

120°

### OPTICS

General

### CONTROL

PWM

### COLOR TYPE

WW

### PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

### CRI

80

### LIGHTING EFFICIENCY (LM/W)

100 lm/W

### POWER (W)

48 W

## INSTALLATION AND MAINTENANCE

### INSTALLATION TYPE

Hardware

## REGULATIONS

### WARRANTY

3 years

## LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT 0	UNITARY PACKAGING WEIGHT UNIT KGM	PACKAGING MEASUREMENT UNIT MMT
UNITARY PACKAGING WIDTH 0	PACKAGING EAN 8421053202746	PACKAGING VOLUME 1200
UNITARY PACKAGING LENGTH 0	UNITS CONTAINED PACKAGING 1	PACKAGING VOLUME UNIT MMQ
UNITARY PACKAGING VOLUME 0	PACKAGING HEIGHT 2	PACKAGING GROSS WEIGHT 412.4
UNITARY PACKAGING GROSS WEIGHT 0.412	PACKAGING WIDTH 24	PACKAGING NET WEIGHT 0.412
PRODUCT NET WEIGHT 0.412	PACKAGING LENGTH 25	PACKAGING WEIGHT UNIT GRM