

Side cover with direct access 2 connectors with 3 poles for aluminium bracket Ofiblock Compacts light grey Simon K45

REF. ACFC04/24



BASIC INFORMATION

DESCRIPTION

Side cover with direct access for 2 connectors with 3 poles for profiles in Ofiblock Compact aluminium light grey in colour of the series Simon K45. It measures 54 x 54 x 3 mm and is fabricated in self-extinguishing halogen-free thermoplastic that guarantees a low toxicity in case of smoke and the no-propagation spread in case of fire. Follow the regulation UNE-EN 60.670-23 and can be installed in places with a temperature of between - 5 to 60 ° C and to clean it, just have to use a dry and soft cloth and never use abrasive cloths or cleaners containing chlorine. The main element of the series Simon K45 Teleblock is its, which presents an automatic elevation that facilitates and solved the needs of connection number, adapting to any type of furniture and closed after connection, it fits perfectly into the furniture, concealing all connections; hand in this position, the role of an aesthetic parades.

FINISH

Light grey

MATERIAL

Plastic

COMPATIBILITY

Ofiblocks Compact and Line
Simon K48

PACKAGING CONTENTS

Side cover with direct access for
2 3-pole quick connect
connectors.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

HEAT RESISTANCE (°C)

+125°C (according to standard IEC 60670)

INSULATION RESISTANCE (V-MΩ)

>5 MOhm at 500 V

IP RATING

IP4X

KIT AVAILABILITY

No

LINKABLE

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

RAL

7035

NUMBER OF SIDE ENTRANCES

2

INSTALLATION AND MAINTENANCE

CABLING ACCESS

Through the housings fitted into the side cover.. Inlet for 3-pole quick connect connectors

REMOVAL OF COMPONENTS

Only with tool

REMOVAL OF COVER

Only with tool

EXTINGUISHING (°C)

+850 °C (according to standard IEC 60670)

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + EN 60670-1:2005

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.007

PACKAGING MEASUREMENT

UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT

UNIT

KGM

PACKAGING VOLUME

911400

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8426436039155

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0.3

UNITS CONTAINED PACKAGING

20

PACKAGING GROSS WEIGHT

0.14

UNITARY PACKAGING VOLUME

UNIT

MMQ

PACKAGING HEIGHT

70

PACKAGING NET WEIGHT

0.14

UNITARY PACKAGING GROSS
WEIGHT

0.007

PACKAGING WIDTH

93

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

140