

## LedFlex 810.52 3000 K IP20 5 mm

REF. 81052000-983



### BASIC INFORMATION

#### APPLICATION

General lighting, Indoor  
decorative lighting

#### PACKAGING CONTENTS

1 unit (5m)

#### ETIM CLASS

EC002706

## TECHNICAL INFORMATION

### IP RATING

IP20

### DRIVER INCLUDED

No

### LUMENS (LM)

6700 lm

### OPERATING TEMPERATURE RANGE (°C)

-20 - 40 °C

### L70 (°C)

30,000 h

### LUMENS/W

6700 lm/72W

### COLOR TEMPERATURE (K)

3000 K

### LIGHT BEAM APERTURE ANGLE (°)

120°

### OPTICS

General

### CONTROL

PWM

### COLOR TYPE

WW

### PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

### CRI

80

### LIGHTING EFFICIENCY (LM/W)

93,1 lm/W

### POWER (W)

72 W

## INSTALLATION AND MAINTENANCE

### INSTALLATION TYPE

Hardware

## REGULATIONS

### WARRANTY

3 years

## LOGISTICS INFORMATION

UNITARY EAN CODE

8421053203071

UNITARY PACKAGING WEIGHT  
UNIT

KGM

PACKAGING MEASUREMENT  
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053203071

PACKAGING VOLUME

1200

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

2

PACKAGING GROSS WEIGHT

140.2

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

24

PACKAGING NET WEIGHT

0.14

UNITARY PACKAGING GROSS  
WEIGHT

0.14

PACKAGING LENGTH

25

PACKAGING WEIGHT UNIT

GRM

PRODUCT NET WEIGHT

0.14