Ofiblock Compact for 4 useful mechanisms with rear diecut in the penultimate position

REF. **KFC104NL1/14**



BASIC INFORMATION

DESCRIPTION

Anodized aluminum Ofiblock Compact profile designed to deliver maximum functionality in a compact size, enabling the convergence of power, voice, data, and multimedia solutions. With its minimal depth and broad range of accessories, it supports multiple installation options on raised floors, walls, furniture, metallic surfaces with magnets, or on DIN rails. Developed to adapt to the specific needs of each space, it allows you to equip it with your personalized configuration of K45 modules, offering a versatile and efficient solution. Supplied with two side covers for quick connectors (Wieland type), providing the Ofiblock Compact with both electrical cable input and output. It also features a rear knockout in the penultimate position for optimal routing of the voice, data, or multimedia cabling connected to the K45 module you decide to install, which will be electromagnetically protected and shielded thanks to the included protective tray. Self-extinguishing, halogen-free thermoplastic covers ensure room safety in the event of a fire.

FINISH

Black

MATERIAL

Metal,Plastic

COMPATIBILITY

Functions of the Simon K45 range and combinable with the Simon Electrical Wiring range.

ETIM CLASS

EC002759

REMARKS

Profile with higher compactness to enable convergence of power, voice, data and multimedia solutions with minimal depth

TECHNICAL INFORMATION

HEAT RESISTANCE (°C)

+125°C (according to standard IEC 60670)

IP RATING

IP4X

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

RAL

7021

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

EXTINGUISHING (°C)

+850 °C (according to standard IEC 60670)

INSTALLATION DIRECTION

Horizontal, Vertical

SECURING POSSIBILITIES

Its design allows it to be surface-mounted on the wall, on table-top furniture, under a desk, on a raised floor, a metal surface with magnet, or on a DIN rail using specific fastening accessories.

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053290484

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.244

PRODUCT NET WEIGHT
0.244

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053290484

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
60

PACKAGING WIDTH
55

PACKAGING LENGTH
275

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
907500

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.278

PACKAGING NET WEIGHT
0.244

PACKAGING WEIGHT UNIT
KGM