

Complete kit with cover, brush, 2 schuko socket outlets, 2 UPS socket outlets and plate for 2 RJ45 connectors black S400 Indesk

REF. 44502220-138



BASIC INFORMATION

DESCRIPTION

Simon offers us a complete kit integrated into the table with a cover and brush, capacity for 2 schukos for standard power, 2 for UPS, and a plate for 2 RJ45 connectors finished in black from the Simon 400 Indesk series. A piece with dimensions of 295 x 185 x 85 millimeters created to perfectly integrate into any space, thanks to its great design and manual lifting system. It has 4 bases for standard power circuit of 250 volts and 16 amperes. As with all Simon products, quality is assured; this kit features an enclosure in painted steel, an anodized aluminum profile, covers, and fasteners in self-extinguishing thermoplastic that guarantee the prevention of flame propagation in case of fire and low toxicity in case of smoke emission.

FINISH

Black

MATERIAL

Metal

COMPATIBILITY

Can be combined with the range of Electric Cabling from Simon.

PACKAGING CONTENTS

Pre-wired profile, enclosure, fastening claws and installation manual.

ETIM CLASS

EC002759

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

INSULATION RESISTANCE (V-MΩ)

>5 MΩ at 500 V

RAL

9005

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

No

CURRENT (A)

16 A

RECESS DIMENSION (MM)

273 x 175 mm (± 2mm)

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the included protective cover and cable outlet with brush

IP RATING

IP30

NUMBER OF RJ45 WINDOWS

2

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT RJ45 PLATES

Keystone I, II and Systimax

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60°C

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 at +60°C

SNAP-FIT TYPE

Keystone I, II and Systimax

FORMAT

Schuko

NOMINAL VOLTAGE (V~)

250 V~

NUMBER OF SOCKETS

2 sockets for standard current circuit and 2 sockets for stable current circuit (UPS)

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

OPERATING TEMPERATURE RANGE (°C)

-5...+60

NUMBER OF UPS SOCKET OUTLETS

2

IK CLASSIFICATION

07

TYPE OF POWER SUPPLY CONNECTOR

Wieland GST 18i male 3-pole overhead connector with 22 cm patch cord

VERSION

5 elements

INSTALLATION AND MAINTENANCE

CABLING ACCESS

With brush

CLAW RANGE OF OPERATION (MM)

Between 20 and 40 mm

NUMBER OF COVER OPENING POSITIONS

1

EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

TYPE OF FASTENING

By tightening existing clamps in the fastening bracket.

REMOVAL OF THE FRAME

Only with tool

INSTALLATION TYPE

Suitable for recessed mount in furniture.

OPENING ORIENTATION

At 45°

SECURING POSSIBILITIES

Using supplied claws or screws in the available holes

MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS

Directiva 2014/35/UE LVD; Directiva 2011/65/UE RoHS; EN 50581:2012; EN 60670-1:2005; EN 60670-1:2005 A1:2013; IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053208205

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053208205

PACKAGING VOLUME

4826250

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

275

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

195

PACKAGING NET WEIGHT

1.95

UNITARY PACKAGING GROSS
WEIGHT

1.95

PACKAGING LENGTH

90

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

1.95