Trim cover for floor trunking distribution baseboards stainless steel Simon Trunking

REF. **KTA904/8**



BASIC INFORMATION

DESCRIPTION

Trim cover for floor trunking distribution baseboards made of stainless steel and that belongs to the series of Simon Trunking. This cover has dimensions of 140 x 140 x 3 mm This is especially designed to distribute the floor trunking. In the case you need adapt it to K45 mini columns taking advantage of the installation of the distribution baseboard, it is advisable to use the cover adapter ALKA02 / 8. Simon Trunking consists of a series of products designed fully adapted to the new trends in the decoration of spaces, maintaining a high degree of aesthetic integration. Therefore, it consists of a fully finish, a metal finish, very used in the market today and that every time it is used in the world of decoration for the brightness and colour that gives the spaces. If you want to keep this trim cover clean and in perfect condition you only need to wipe it with a soft and dry cloth, taking into account that you must never use abrasive cloths or cleaners containing chlorine in their formulation as it could get damaged.

FINISH

Metal

MATERIAL

Stainless steel

COMPATIBILITY

Distribution sockets Simon Trunking

PACKAGING CONTENTS

Trim cover for floor trunking distribution baseboards, ground connection cable, screws and installation manual

ETIM CLASS

EC002417

REMARKS

Specifically designed cover for distributing floor trunking. In the event of needing to adapt K45 mini columns taking advantage of the distribution baseboard installation, it is recommended to use the ALKA02/8 adaptor cover.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

DIELECTRIC STRENGTH
Without perforation or contournament with 2000 V at 50H during 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)
+120° C

EARTHING RESISTANCE
< 0.05 ?

ELECTRICAL PROPERTIES
With electrical continuity

HEAT RESISTANCE (°C)
+850°C (according rule IEC 60695-10-2)

INSULATION RESISTANCE (V-MΩ)
5 MOhms at 500 V.

IP RATING
IP4X

KIT AVAILABILITY
No

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60° C

INSTALLATION AND MAINTENANCE

REMOVAL OF COVER
Only with tool

TYPE OF FASTENING
Using supplied screws

INSTALLATION DIRECTION
Horizontal

REGULATIONS

REGULATIONS
Directive 2014/35/UE LVD + EN 50085-2-2:2008

LOGISTICS INFORMATION

UNITARY EAN CODE
8426436035447

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
422500

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.105

PRODUCT NET WEIGHT
0.105

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436035447

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
25

PACKAGING WIDTH
130

PACKAGING LENGTH
130

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
422500

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.105

PACKAGING NET WEIGHT
0.105

PACKAGING WEIGHT UNIT
KGM