

## Euro-American socket gloss black Simon 100

REF. 10000439-138



### BASIC INFORMATION

#### FINISH

Gloss black

#### COMPATIBILITY

Frames Simon 100

#### ETIM CLASS

EC000125

## TECHNICAL INFORMATION

|                                                          |                                                                                                                            |                                                      |
|----------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------|
| <b>AVAILABLE MARKET</b><br>CE                            | <b>CURRENT (A)</b><br>16 A                                                                                                 | <b>NOMINAL VOLTAGE (V~)</b><br>127/250 V~            |
| <b>CABLE SECTION ADMITTED (MM)</b><br>From 1,5 to 2,5 mm | <b>IP RATING</b><br>IP20                                                                                                   | <b>OPERATING TEMPERATURE RANGE (°C)</b><br>0 - 40 °C |
| <b>NUMBER OF POSSIBLE ELEMENTS</b><br>1 element          | <b>MAINTENANCE</b><br>Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine. | <b>POWER SUPPLY (V~)</b><br>127/250 V~               |
| <b>FORMAT</b><br>Euro-American                           | <b>TYPE OF MECHANISM</b><br>Insertion                                                                                      | <b>STORAGE TEMPERATURE RANGE (°C)</b><br>-25 - 75 °C |
| <b>INDICATOR FUNCTION</b><br>No                          | <b>MONOBLOCK</b><br>No                                                                                                     | <b>VERSION</b><br>Unique                             |

## INSTALLATION AND MAINTENANCE

|                                             |                                                             |                                                          |
|---------------------------------------------|-------------------------------------------------------------|----------------------------------------------------------|
| <b>CABLE STRIPPING NECESSARY (MM)</b><br>10 | <b>INSTALLABLE IN FLUSH MOUNT JUNCTION BOX</b><br>universal | <b>INSTALLATION TYPE</b><br>Suitable for flush mounting  |
| <b>CLAW</b>                                 | <b>INSTALLATION DIRECTION</b><br>Horizontal, Vertical       | <b>TYPE OF TERMINAL CONNECTION - FUNCTION 1</b><br>Screw |

## REGULATIONS

### REGULATIONS

IEC 60884-1 Ed 3.2 + NMX-J-412-1-ANCE 2011 + NMX-J-163-ANCE 2004 + IEC 60884-1 Ed 3.2 + NMX-J-412-1-ANCE 2011 + NMX-J-163-ANCE 2004

## LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT  
0

UNITARY PACKAGING WEIGHT  
UNIT  
KGM

PACKAGING MEASUREMENT  
UNIT  
MMT

UNITARY PACKAGING WIDTH  
0

PACKAGING EAN  
8421053192283

PACKAGING VOLUME  
1042800

UNITARY PACKAGING LENGTH  
0

UNITS CONTAINED PACKAGING  
5

PACKAGING VOLUME UNIT  
MMQ

UNITARY PACKAGING VOLUME  
0

PACKAGING HEIGHT  
75

PACKAGING GROSS WEIGHT  
0.255

UNITARY PACKAGING GROSS  
WEIGHT  
0.026

PACKAGING WIDTH  
88

PACKAGING NET WEIGHT  
0.13

PRODUCT NET WEIGHT  
0.026

PACKAGING LENGTH  
158

PACKAGING WEIGHT UNIT  
KGM

