

French double socket outlet 16A 250V~ with safety device and 1Click® terminal connection graphite Simon 500 Cima

REF. 50000468-038



BASIC INFORMATION

DESCRIPTION

Suitable for surface and flush mounting, the Socket-outlet for ground connection in French double switch with 16 AX current and 250V~ voltage, safety device and click terminal connection in graphite finish in one of the best-selling elements of the included in the catalogue of the Simon 500 Cima series. This is a accessory with a cable section of 1.5 to 2.5 mm, dimensions of 100 x 50 mm and a depth of 46 mm This socket outlet has been manufactured by metal components with self-extinguishing, halogen-free thermoplastic insulation, which guarantees no flame propagation in case of fire and the low toxicity in case of smoke, so this is a piece that is ideal for public and private buildings with a large influx of people.

FINISH

Graphite

PACKAGING CONTENTS

Double socket outlet with cover
and installation manual

ETIM CLASS

EC000125

COMPATIBILITY

Simon 500 Cima enclosures

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

NUMBER OF CONNECTIONS PER TERMINAL

1 terminal connection for click terminal connection system and 2 terminal connections for screw terminal connection system

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

FORMAT

French

HEAT RESISTANCE (°C)

+125°C (according rule IEC 60695-10-2)

INDICATOR FUNCTION

No

INSULATION RESISTANCE (V-MΩ)

>5MΩ at 500V

CURRENT (A)

16 A

IP RATING

IP20

LINKABLE

Yes, using accessory 50000996-039

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-25 to 60 °C

TYPE OF MECHANISM

Insertion

NUMBER OF MODULES

2

MONOBLOCK

No

NOMINAL VOLTAGE (V~)

250 V~

RAL

7021

NUMBER OF SOCKETS

2

VERSION

Double

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

0

REMOVAL OF COVER

Only with tool

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-10-2)

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Horizontal, Vertical

INSTALLATION TYPE

Suitable for surface and flush mounting

REMOVAL OF THE SOCKET

Only with tool

TYPE OF TERMINAL CONNECTION - FUNCTION 1

1 click connection (1 click®)

NUMBER OF TERMINALS

3 inputs and 3 outputs

REGULATIONS

REGULATIONS

Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | IEC 60884-1 Ed. 3.2 | UNE 20315-1-1:2017 | UNE 20315-1-2:2017 | DS 60884-2-D1:2023

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT	UNITARY PACKAGING WEIGHT	PACKAGING MEASUREMENT
0	UNIT	UNIT
	KGM	MMT
UNITARY PACKAGING WIDTH	PACKAGING EAN	PACKAGING VOLUME
0	8421053106402	3.525
UNITARY PACKAGING LENGTH	UNITS CONTAINED PACKAGING	PACKAGING VOLUME UNIT
0	10	DMQ
UNITARY PACKAGING VOLUME	PACKAGING HEIGHT	PACKAGING GROSS WEIGHT
0	112	0
UNITARY PACKAGING GROSS WEIGHT	PACKAGING WIDTH	PACKAGING NET WEIGHT
0.111	117	1.11
PRODUCT NET WEIGHT	PACKAGING LENGTH	PACKAGING WEIGHT UNIT
0.111	269	KGM

