

Modular Luminaire 720 Advance M2 60x60 NW 1-10V

REF. 72060120-884



BASIC INFORMATION

DESCRIPTION

We have the Luminaire 720 modular Advance M2 60x60 NW 1-10V, a light source neutral of 3000° Kelvin with a high light output of over 100 lumens by vatio. Its optics translucida allows better light optimisation. This is a product finished in white, especially manufactured for installation in false ceiling with profile. Its measures are 595 x 595 x 60 millimetres with a power of 18 Watts. The luminaires of the series Simon 720 Advance stand out for their energy efficiency and its durability. It offers us a minimum of 40,000 hours of constant light in terms of 25 ° centigrade. If we are talking about savings, this luminaire it offers us a reduction of 50% of the consumption, as they are specially designed to use the minimum of solar light to achieve a lighting of great quality.

DIFFUSER MATERIAL

PMMA

PACKAGING CONTENTS

1 unit

APPLICATION

General lighting

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DRIVER INCLUDED

Yes

LIGHTING EFFICIENCY (LM/W)

139 lm/W

IP RATING

IP44

ELECTRICAL CLASS

Tipo 2

LUMENS (LM)

2500 lm

OPERATING TEMPERATURE RANGE (°C)

40 °C maximum

INTEGRATED POWER SUPPLY

Yes

LUMENS/W

2500 lm/18W

POWER SUPPLY (V~)

100/240 V~

L70 (°C)

100,000 h at 25 °C

OPTICS

Translucent

COLOR TEMPERATURE (K)

4000 K

L90 (°C)

40,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempted category

CONTROL

1-10 V

LIGHT BEAM APERTURE ANGLE (°)

120°

POWER (W)

18 W

CRI

82

COLOR TYPE

NW

SERVICE LIFE

50.000 h

CHROMATICS CRI ICONS

CRI
82

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Plaster ceiling, surface mount, concealed or semi-concealed profile.

MINIMUM INSTALLATION HEIGHT

120

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Quick connector

INSTALLATION TYPE

False ceiling, visible hardware

REGULATIONS

WARRANTY

5 years 50,000 h

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

5.66

PRODUCT NET WEIGHT

5

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053124741

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

65

PACKAGING WIDTH

600

PACKAGING LENGTH

600

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

0.234

PACKAGING VOLUME UNIT

HLT

PACKAGING GROSS WEIGHT

5.66

PACKAGING NET WEIGHT

5

PACKAGING WEIGHT UNIT

KGM