

Metal tray for adjustable floor box for 8 elements for installation in concrete floor Simon 500 Cima

REF. 52052204-033



BASIC INFORMATION

DESCRIPTION

This kit is part of the series of Simon 500 Cima and contains all the necessary for the installation of a adjustable floor box. The box is specially designed to be located by recessing in a very simple way in concrete floors, although it is also could adapt perfectly to the raised floor. Supplies energy to a total of 8 elements of up to 16 A and 250 volts. The elements that make up in kit are 2 double socket, 2 plates 2RJ45 and a power uninterrupted system, which guarantees in operation of the box even in case of power outage by a time limited. So that the final set perfect will have to be combined with a plastic tray with reference Simon 52052104-035, and as optionally with the flush-mount trim with reference ref.52053104-035. The box is made up of 8 modules, has dimensions of 187 x 283 millimetres and 76 millimetres of depth and comes in an original grey colour that endow elegance to any room where it is. The components with which it has been manufactured the product are components with halogen-free thermoplastic insulation, which makes the set very safe as is capable of extinguishing the flames in case of fire and reduces the toxicity of smoke.

FINISH

Aluminium

PACKAGING CONTENTS

Tray, protective cover, floor fixing screws and installation manual

ETIM CLASS

EC000114

MATERIAL

Steel

REMARKS

To complete the installation of the product, it must be combined with a concrete floor box for 8 elements in a grey (ref.52050004-035) or graphite finish (ref.52050004-038).

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

IP RATING

IP4X

RECESS DIMENSION (MM)

363 x 363 mm

AVAILABLE IN

6, 8 and 12 elements

KIT AVAILABILITY

No

VERSION

8 elements

MAX TEMP DURING CONSTRUCTION WORK (°C)

+90 °C

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

IK CLASSIFICATION

08

NUMBER OF MODULES

8 modules

INSTALLATION AND MAINTENANCE

NUMBER OF CHANNEL ENTRIES

4

INSTALLATION DIRECTION

Circular

SCREWS REQUIRED FOR SLAB FIXING

Minimum 2 (1 per side, diagonally). It is recommended to fix the bowl with 4 screws for complete fixation.

TYPE OF FASTENING

Using the screws supplied

INSTALLATION TYPE

Specially designed for installation in concrete floors

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + EN 60670-23:2008

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053101773

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053101773

PACKAGING VOLUME

0.111

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

HLT

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

375

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

80

PACKAGING NET WEIGHT

5.315

UNITARY PACKAGING GROSS
WEIGHT

5.315

PACKAGING LENGTH

370

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

5.315



