

German monoblock socket outlet 16A 250V~ with safety device and screw terminal connection system white Simon 82

REF. 82452-30



BASIC INFORMATION

FINISH

White

PACKAGING CONTENTS

Socket outlet with cover and frame

ETIM CLASS

EC000125

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CURRENT (A)

16 A

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

CABLE SECTION ADMITTED (MM)

2,5 mm

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

NUMBER OF POSSIBLE ELEMENTS

1 element

TYPE OF MECHANISM

Insertion

VERSION

Single

FORMAT

Schuko

VOLTAGE (V~)

250 V~

INDICATOR FUNCTION

No

MONOBLOCK

Yes

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

13

INSTALLATION TYPE

Suitable for surface and flush mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

INSTALLATION DIRECTION

Horizontal, Vertical

REGULATIONS

REGULATIONS

UNE 20315-1-1:2009, UNE 20315-1-2:2009

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
3685500

UNITARY PACKAGING VOLUME
UNIT
MMQ

UNITARY PACKAGING GROSS
WEIGHT
0.122

PRODUCT NET WEIGHT
0.122

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING EAN
8421053029305

UNITS CONTAINED PACKAGING
10

PACKAGING HEIGHT
91

PACKAGING WIDTH
180

PACKAGING LENGTH
225

PACKAGING MEASUREMENT
UNIT
MMT

PACKAGING VOLUME
3685500

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
1.22

PACKAGING NET WEIGHT
1.22

PACKAGING WEIGHT UNIT
KGM