

Modular luminaire 726 60x60 4000K 5Y

REF. 72680033-884



BASIC INFORMATION

APPLICATION

General lighting, Office

ETIM CLASS

EC002892

TECHNICAL INFORMATION

IP RATING

IP20

COLOR TEMPERATURE (K)

4000 K

CRI

80

L70 (°C)

36.000 h a 25°C

LIGHT BEAM APERTURE ANGLE (°)

120°

LIGHTING EFFICIENCY (LM/W)

98,46 lm/W

LUMENS (LM)

3840 lm

OPTICS

General

PHOTOBIOLOGICAL CLASSIFICATION

Exempted category

POWER (W)

39 W

SERVICE LIFE

50.000 h

CHROMATICS CRI ICONS

CRI
80

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053285800

UNITARY PACKAGING HEIGHT

60

UNITARY PACKAGING WIDTH

740

UNITARY PACKAGING LENGTH

640

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

28416000

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

3

PRODUCT NET WEIGHT

2.8

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053285800

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

60

PACKAGING WIDTH

740

PACKAGING LENGTH

640

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

28416000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

3

PACKAGING NET WEIGHT

2.8

PACKAGING WEIGHT UNIT

KGM