2-way switch 10AX 250V~ with built-in pilot light and fast terminal connection system white Simon 27 Play

REF. **27212-65**



BASIC INFORMATION

DESCRIPTION

Comutador de 16AX de intensidade e que requer uma potência de 250 V~ com piloto incorporado e que inclui um sistema ligação rápida de bornes fabricado com um acabamento em cor branco e que poderás encontrar na série Simon 27 Play. Com a premissa que oferece a coleção desfrutarás decorando e é por isso que o elemento é combinável com a referência 31802-31 em caso de substituição de indicador luminoso.

Beneficia de todas as funções que oferece a série Simon 27 Play para teus elementos, te dando a possibilidade aproveitar um conceito revolucionário que permite tomar a iniciativa na hora de redecorar a cada um dos espaços da tua habitação. O espelho é combinável com 7 acabamentos para peças intermédias, 5 acabamentos para tampas articuláveis e outros 5 acabamentos para teclas permutáveis.

FINISH

White

COMPATIBILITY

Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations and Simon 44 Aqua frames

PACKAGING CONTENTS

Mechanism with rocker

ETIM CLASS

EC001590

REMARKS

Can be combined with article 31802-31 if replacing the light indicator.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

CONSUMPTION INDICATOR (MA)

0.55 mA

NUMBER OF POSSIBLE ELEMENTS

1 element

INDICATOR FUNCTION

Yes

CURRENT (A)

16 AX

IP RATING

IP20

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TYPE OF MECHANISM

Pivoting

NOMINAL VOLTAGE (V~)

250 V~

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

VERSION

Single

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)
11

CLAW
Simon 27

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, American and Centralisations

INSTALLATION DIRECTION
Horizontal, Vertical

INSTALLATION TYPE
Suitable for surface and flush mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1
Fast

REGULATIONS

REGULATIONS
Dir. 2014/35/UE LVD|Dir. 2011/65/UE RoHS + post. mod.|EN 60669-1:2018|EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
1235960

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.036

PRODUCT NET WEIGHT
0.036

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053035696

UNITS CONTAINED PACKAGING
10

PACKAGING HEIGHT
53

PACKAGING WIDTH
106

PACKAGING LENGTH
220

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
1235960

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.36

PACKAGING NET WEIGHT
0.36

PACKAGING WEIGHT UNIT
KGM