

**Set of 2 push buttons 10A 250V~ (2 inputs+2 outputs)  
mech.blinds without latching sys. with fast terminal  
connection ivory Simon 31**

REF. 31396-31



## BASIC INFORMATION

### DESCRIPTION

Unit of two push buttons with 2 inputs and 2 outputs for blinds, in ivory colour and without latching system (so it requires a control device), belonging to the Simon 31 series. It has a quick terminal connection and a rocker operation and a voltage of 250V and an current of 10 AM. It has 2 modules and supports a cable section of 1.5 to 2.5 mm, with a stripping of 11 mm and can be installed in rooms with a temperature located between 5 and 40°C, although it's true that works also perfectly in places with a temperature of -25 to 50°C, approximately. Its design is in compliance with regulations UNE-EN 60669-1:2002 + A1:2003 + A2:2009 and is manufactured with metal components with halogen-free thermoplastic insulation and trim made of thermoplastic. It measures 64x65 mm and is easily cleaned by wiping it gently with a soft cloth moistened in soapy water.

### FINISH

Ivory

### COMPATIBILITY

Simon 31 frames

### ETIM CLASS

EC000029

### MATERIAL

Thermoplastic

### PACKAGING CONTENTS

Mechanism with rocker

### REMARKS

Mechanism with no latching. Requires control device.

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE

### CURRENT (A)

10 AX

### TYPE OF MECHANISM

Pivoting

### CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

### IP RATING

IP21

### OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

### NUMBER OF POSSIBLE ELEMENTS

1 element

### LATCH TYPE

Non-latching

### STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

### INDICATOR FUNCTION

No

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### VERSION

Double

## INSTALLATION AND MAINTENANCE

### CABLE STRIPPING NECESSARY (MM)

11

### INSTALLATION TYPE

Suitable for surface and flush  
mounting

### INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

### TYPE OF TERMINAL CONNECTION - FUNCTION 1

Fast

## REGULATIONS

### REGULATIONS

UNE-EN 60669-1:2002 + A1:2003 + A2:2009

## LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT  
0

UNITARY PACKAGING WIDTH  
0

UNITARY PACKAGING LENGTH  
0

UNITARY PACKAGING VOLUME  
3026595

UNITARY PACKAGING VOLUME  
UNIT  
MMQ

UNITARY PACKAGING GROSS  
WEIGHT  
0.095

PRODUCT NET WEIGHT  
0.095

UNITARY PACKAGING WEIGHT  
UNIT  
KGM

PACKAGING EAN  
8421053052075

UNITS CONTAINED PACKAGING  
10

PACKAGING HEIGHT  
83

PACKAGING WIDTH  
165

PACKAGING LENGTH  
221

PACKAGING MEASUREMENT  
UNIT  
MMT

PACKAGING VOLUME  
3026595

PACKAGING VOLUME UNIT  
MMQ

PACKAGING GROSS WEIGHT  
0.95

PACKAGING NET WEIGHT  
0.95

PACKAGING WEIGHT UNIT  
KGM