

Inspection cover for 3 double modules for installation on pavement or technical floor in graphite Simon Cima

REF. S300/14



BASIC INFORMATION

FINISH

Graphite

MATERIAL

Various

COMPATIBILITY

With plastic and metallic buckets of 3 double elements Simon Cima when installed on pavement floor.

ETIM CLASS

EC001903

TECHNICAL INFORMATION

HEAT RESISTANCE (°C)

+125 °C (in accordance with standard IEC 60695-10-2)

IK CLASSIFICATION

08

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

RAL

7021

RECESS DIMENSION (MM)

170 x 210 mm

INSTALLATION AND MAINTENANCE

NUMBER OF COVER OPENING POSITIONS

2

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

CAN BE INSTALLED IN TRAY

Plástica y metálica

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436020436

PRODUCT NET WEIGHT

1.005

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

3152700

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8426436020436

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

1.005

UNITARY PACKAGING VOLUME

3152700

PACKAGING HEIGHT

75

PACKAGING NET WEIGHT

1.005

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

186

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

1.005

PACKAGING LENGTH

226