

German monoblock socket outlet 16A 250V~ with safety device and screw terminal connection aluminium Simon 31

REF. 31472-63



BASIC INFORMATION

DESCRIPTION

Schuko socket outlet monobloc of the series Simon 31, in aluminium colour and with safety device and screw terminal connection system. Its current is 16 A and works with a voltage of 250V, in addition to work by insertion. The covers with the that comes this socket-outlet include the child protection function. It has 2 modules, supports a section of wire 2.5 mm, with a stripping of the 13 mm and can be position, place, perfectly in rooms with a temperature located between 5 and 40°C, although it is able to withstand extreme temperatures of -25 to 50°C, approximately. Complies with the European standards and regulations UNE 20315-1-1: 2009, UNE 20315-1-2: 2009 and is manufactured with metal components with halogen-free insulation and thermoplastic metallized caps. Its dimensions are 87x87 mm and to clean it, just need a soft, dry cloth and never use abrasive cloths or cleaners containing chlorine.

FINISH

Aluminium

PACKAGING CONTENTS

Socket outlet with cover and frame

ETIM CLASS

EC000125

REMARKS

The covers include a child-proof protective feature.

TECHNICAL INFORMATION

AVAILABLE MARKET CE	CURRENT (A) 16 A	MONOBLOCK Yes
CABLE SECTION ADMITTED (MM) 2,5 mm	IP RATING IP21	OPERATING TEMPERATURE RANGE (°C) 5 - 40 °C
NUMBER OF POSSIBLE ELEMENTS 1 element	MAINTENANCE Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.	STORAGE TEMPERATURE RANGE (°C) -25 - 50 °C
FORMAT Schuko	TYPE OF MECHANISM Insertion	VERSION Single
INDICATOR FUNCTION No		VOLTAGE (V~) 250 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM) 13	INSTALLATION TYPE Suitable for surface and flush mounting
INSTALLABLE IN FLUSH MOUNT JUNCTION BOX Universal	TYPE OF TERMINAL CONNECTION - FUNCTION 1 Screw

REGULATIONS

REGULATIONS

UNE 20315-1-1:2009, UNE 20315-1-2:2009

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
3685500

UNITARY PACKAGING VOLUME
UNIT
MMQ

UNITARY PACKAGING GROSS
WEIGHT
0.125

PRODUCT NET WEIGHT
0.125

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING EAN
8421053071823

UNITS CONTAINED PACKAGING
10

PACKAGING HEIGHT
91

PACKAGING WIDTH
180

PACKAGING LENGTH
225

PACKAGING MEASUREMENT
UNIT
MMT

PACKAGING VOLUME
3.685

PACKAGING VOLUME UNIT
DMQ

PACKAGING GROSS WEIGHT
1.245

PACKAGING NET WEIGHT
1.25

PACKAGING WEIGHT UNIT
KGM