

PD-6x6 PIR+LUX recessed box DALI-2 Input white IP20

REF. 89212321-130



BASIC INFORMATION

DESCRIPTION

PIR flush-mounted motion and light detector. The recommended installation height is 2.8 m, with a maximum height of 5 m. It has a detection angle of 360° and an opening angle of 160°. The tangential detection range is 6 x 6 m and the radial detection range is 4 x 4 m.

The light regulation range is 2 - 1000 lux. The detector configuration is done via DALI.

Possibility of interconnection between sensors through DALI. The control protocol is DALI-2 Input. The typical consumption is 4 mA.

The power supply voltage is DALI (12 - 20.5 VDC). The operating temperature of the detector is: 0 - 40 °C. White finish, IP 20 protection degree and dimensions: Ø 80 x 21 mm.

5-year warranty

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

TECHNICAL INFORMATION

IP RATING

IP20

RAL

9003

POWER SUPPLY (V~)

DALI bus (12 Vdc – 20,5 Vdc)

CONTROL

DALI2 Slave

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053356661

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.092

PRODUCT NET WEIGHT

0.039

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053356661

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

132

PACKAGING WIDTH

46

PACKAGING LENGTH

91

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

552552

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.092

PACKAGING NET WEIGHT

0.039

PACKAGING WEIGHT UNIT

KGM