

## Customisable set with 1 schuko socket outlet and 5 empty elements black S400 Top

REF. 42601000-138



## BASIC INFORMATION

### DESCRIPTION

With the kit of desk top customizable of the collection Simon 400 Top, you will get the maximum functionality of its devices connected in the minimum space compact. With a design of simple lines and finishes in black, this kit consists of 1 Schuko socket-outlet and 5 empty elements for that includes the application-specific functions that requires the room. Ideal for working areas, the kit is designed for flush installation, fitted with clamps pages, and has a size of 295 x 120 x 80 mm Compatible with a voltage of 250 V and current of 16 A, its dielectric strength is 2000 V at 50H per minute and has a insulation resistance > 5 M $\Omega$  at 500 V. This kit is connected to a figure Wieland gst 18i with 3-pole male in-line and patch cord of 22 cm. Made of anodised aluminium and thermoplastic self-extinguishing halogen-free, protects the room in case of fire and prevents the flame spread and toxicity by smoke.

### FINISH

Black

### MATERIAL

Metal

### COMPATIBILITY

Functions of the Simon 400 range, combinable with the Simon Electric Cabling range.

### PACKAGING CONTENTS

Pre-wired profile, table-top supports, rear trim cover and installation manual.

### ETIM CLASS

EC002759

### REMARKS

To complete the product installation combine it with the Simon 400 functions (refs. 400XXXXX-03X).

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE

### DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

### MAX TEMP DURING CONSTRUCTION WORK (°C)

+60  C

### NUMBER OF POSSIBLE ELEMENTS

5

### FORMAT

Schuko

### HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

### INSULATION RESISTANCE (V-MΩ)

>5 M? at 500 V

### CURRENT (A)

16 A

### IP RATING

IP30

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 at +60  C

### TYPE OF POWER SUPPLY CONNECTOR

Wieland  GST 18i male 3-pole overhead connector with 22 cm patch cord

### RAL

9005

### NUMBER OF REAR ENTRANCES

5

### NUMBER OF SOCKETS

1 socket for standard current circuit

### VERSION

6 elements

### VOLTAGE (V~)

250 V~

## INSTALLATION AND MAINTENANCE

### CLAW RANGE OF OPERATION (MM)

Between 16 and 40 mm

### REMOVAL OF COMPONENTS

### EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

### TYPE OF FASTENING

By tightening existing clamps in the fastening bracket.

### INSTALLATION TYPE

Suitable for fixing to furniture.

### REMOVAL OF THE PLATE

Only with tool

### SECURING POSSIBILITIES

Using clips included in the fastening brackets

### MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

## REGULATIONS

### REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053196007

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING GROSS WEIGHT

0.835

### PRODUCT NET WEIGHT

0.835

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053196007

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

330

### PACKAGING WIDTH

125

### PACKAGING LENGTH

95

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

3918750

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

0

### PACKAGING NET WEIGHT

0.835

### PACKAGING WEIGHT UNIT

KGM