

Flush-mount wall frame and frame holder for 1 double element white Simon 500 Cima

REF. 51010101-030



BASIC INFORMATION

FINISH

White

MATERIAL

Plastic

COMPATIBILITY

Simon 500 Cima and Simon 27 Play/Simon K45 mechanisms (using specific adaptors), combinable with the Simon Trunking range

PACKAGING CONTENTS

Flush-mount wall frame, frame holder and installation manual

ETIM CLASS

EC000007

REMARKS

Optionally, the frame holder can be screwed on to the box if a more secure installation is required.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

HEAT RESISTANCE (°C)

+125°C (according rule IEC 60695-10-2)

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

AVAILABLE IN

1, 2, 3, 4 and 6 double elements

IK CLASSIFICATION

07

NUMBER OF MODULES

2

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

INSULATION RESISTANCE (V-MΩ)

>5MΩ at 500V

RAL

9003

MAX TEMP DURING CONSTRUCTION WORK (°C)

+90 °C

IP RATING

IP4X

RECESS DIMENSION (MM)

141 x 73 mm

ELECTROMAGNETIC IMMUNITY FOR VDM WIRING

Secured by installing the metal partition wall in the housing fitted into the box for this purpose.

KIT AVAILABILITY

No

VERSION

1 double element

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

TYPE OF FASTENING

By direct snap-fit in the selected box (no tools needed for fastening)

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

REMOVAL OF THE FRAME

Only with tool

INSTALLATION TYPE

Suitable for flush mounting on the wall

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + EN 60670-1:2005

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053091739

PACKAGING VOLUME

5.61

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

10

PACKAGING VOLUME UNIT

DMQ

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

170

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING GROSS WEIGHT

0.114

PACKAGING WIDTH

165

PACKAGING NET WEIGHT

1.14

PRODUCT NET WEIGHT

0.114

PACKAGING LENGTH

200

PACKAGING WEIGHT UNIT

KGM

