

Back kit for 2 elements with 1 two-way push-button switch, 1 USB charger and 1 Schuko socket outlet Simon 100

REF. 10010206-039



BASIC INFORMATION

DESCRIPTION

This kit rear is part of the Simon 100 series and is designed as lighting point for two electrical elements of up to 16 A and 250 volts. On this occasion, the back kit is 2-way switch with a push button, a socket outlet base and a USB charger, so that stands out for its versatility and high functionality. The 2-way switch push button is ideal to allow the switching on the light from two different places, something common, for example, in bedrooms where it is located a system of switching on to the input of the room and other together with the headboard to increase the comfort of the user. It has a click terminal system, in the case of the plug and the 2-way switch, and screw for the USB. The operation is also very simple, consisting of a tilting push-button switch that facilitates interaction.

FINISH

Black

COMPATIBILITY

Front Kit Simon 100

ETIM CLASS

EC002846

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

IP RATING

IP20

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

NUMBER OF POSSIBLE ELEMENTS

2 elements

TYPE OF MECHANISM

Push button rocker switch/Insertion

USB CHARACTERISTICS

10W

FORMAT

Schuko,USB

MONOBLOCK

No

USB CURRENT (A)

2,1 A

INDICATOR FUNCTION

No

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

USB VOLTAGE (V~)

5 Vdc

CURRENT (A)

10 AX

POWER SUPPLY (V~)

250 V~

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

INSTALLATION DIRECTION

Horizontal

KIT INSTALLATION DIRECTION

Horizontal

TYPE OF TERMINAL CONNECTION - FUNCTION 2

USB: Screw

INSTALLATION TYPE

Suitable for flush mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Schuko/2-way Switch: 1 click connection (1 click®)

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2014/30/UE EMC + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60950-1:2006 + EN 60950-1:2006 A11:2009 + EN 60950-1:2006 A1:2010 + EN 60950-1:2006 A12:2011 + EN 60950-1:2006 A2:2011*3 + EN 60669-1:1999 + EN 60669-1:1999 A1:2002 + EN 60669-1:1999 A2: 2008*2 + ETSI-EN 301489-34 v14.1*3 + IEC 60884-1 Ed. 3.2*1

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053147795

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.253

PRODUCT NET WEIGHT

0.253

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053147795

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

75

PACKAGING WIDTH

88

PACKAGING LENGTH

158

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

1042800

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

252.8

PACKAGING NET WEIGHT

0.253

PACKAGING WEIGHT UNIT

GRM