

## Rocker with viewer for push button switch with indicator light function for 1 element black Simon K45

REF. K114/14



## BASIC INFORMATION

### DESCRIPTION

Use their electric mechanism in situations with low lighting with rocker with viewer for push-button switch with incorporated indicator light from the Simon K45 collection with a black finish and a compact size 45 x 45 mm and 10 mm depth, guaranteeing the integration of the set in all types of spaces, adding a style current and simple, suitable for all types of environments and decorative styles. It is designed for installation both flush mounted and surface-mounted, which maximize the versatility of the product, allowing you to adapt to the specific needs of each space. Manufactured with thermoplastic materials halogen-free, prevents the flame spread and toxicity by smoke in case of fire, and can reach maximum temperatures of more than 60 °C.

### FINISH

Black

### MATERIAL

Plastic

### COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-038)

### PACKAGING CONTENTS

Rocker and installation manual

### ETIM CLASS

EC000011

### REMARKS

Used to signal the mechanism and spot it in the dark

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE

### IP RATING

IP20

### TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

### AVAILABLE IN

Quarter and half module versions

### KIT AVAILABILITY

No

### NUMBER OF MODULES

Half

### MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### RAL

7021

### INDICATOR FUNCTION

Yes

### VERSION

Single

## INSTALLATION AND MAINTENANCE

### REMOVAL OF COVER

Only with tool

### TYPE OF FASTENING

Fixing by direct snap-fit, no tools needed

### INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-038)

### INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

### INSTALLATION TYPE

Suitable for surface and flush mounting

## REGULATIONS

### REGULATIONS

Directive 2014/35/UE LVD + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60669-1:1999 + EN 60669-1:1999 A1:2002 + EN 60669-1:1999 A2:2008

## LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.01

PACKAGING MEASUREMENT  
UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT  
UNIT

KGM

PACKAGING VOLUME

590625

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8426436047143

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0.3

UNITS CONTAINED PACKAGING

10

PACKAGING GROSS WEIGHT

0.96

UNITARY PACKAGING VOLUME  
UNIT

MMQ

PACKAGING HEIGHT

75

PACKAGING NET WEIGHT

0.1

UNITARY PACKAGING GROSS  
WEIGHT

0.01

PACKAGING WIDTH

105

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

75