

Push/pull module for Teleblock telescopic profiles with manual elevation Simon K45

REF. KTLA3



BASIC INFORMATION

DESCRIPTION

Push-pull module for telescopic profiles with manual elevation for Teleblock of the series Simon K45. It is manufactured in self-extinguishing halogen-free thermoplastic; guarantees no flame propagation in case of fire and the low toxicity in case of smoke and finished in black colour and its type is manual elevation. Its design follows the UNE-EN 60.670-23. It can withstand temperatures of -5 to 60 ° C The Simon K45 Teleblock solved the needs of connection number, adapting to any type of furniture and offers an automatic elevation that gives it a single of avant-garde technology, in addition to a design and originality to make this Teleblock on an image object of high level. Integration offers a perfect adaptation of the space in which it is located at the look hidden, if you want since it you can have the cables are sorted and hidden.

FINISH

Black

MATERIAL

Plastic

COMPATIBILITY

Teleblock with manual elevation from the Simon K45 range.

PACKAGING CONTENTS

Push-pull module and installation manual.

ETIM CLASS

EC002649

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DIELECTRIC STRENGTH

Without perforation or
contournement with 2000 V at
50H during 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

HEAT RESISTANCE (°C)

+70°C (according to standard IEC
60670)

INSULATION RESISTANCE (V-MΩ)

>5 MOhm at 500 V

IP RATING

IP4X

KIT AVAILABILITY

No

LINKABLE

No

MAINTENANCE

Clean with a soft, dry cloth. Do
not use abrasive cloths or
cleaning products that contain
chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

RAL

7021

INSTALLATION AND MAINTENANCE

EXTINGUISHING (°C)

+850 °C (according to standard
IEC 60670)

TYPE OF FASTENING

By snap-fitting the module on to
the Simon K45 Teleblock
telescopic profile Note: this
article is a replacement part and
is supplied with the Simon K45
Teleblock telescopic profile.

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60670-1:2005

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436051669

PRODUCT NET WEIGHT

0.045

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

544320

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8426436051669

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.045

UNITARY PACKAGING VOLUME

544320

PACKAGING HEIGHT

72

PACKAGING NET WEIGHT

0.045

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

72

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

0.045

PACKAGING LENGTH

105